

VT65ML7BIIF



33.5" x 23.63" x 23.5" (H x W x D)

Commercial built-in medical all-freezer capable of -25° C operation with front lock; door accepts full overlay panels

Highlights:

Flexible design allows built-in or freestanding use

-25° C operation for safe storage of temperature sensitive materials

Three slide-out freezer drawers help contents maintain stable temperature, even with an open door

Product Features:

Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter
Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Fully finished white cabinet	Allows the unit to be used freestanding
Factory installed lock	Keyed lock for a secure interior
Integrated door frame	Customize the front by mounting an overlay panel over the door; seamless look can blend into cabinetry with no exposed frame. Handle not included. (panel dimensions: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static cooling system for improved temperature stability
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened
Adjustable thermostat	Manage the temperature with ease and accuracy

VT65ML7BIIF Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Shipping Weight	118.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101043180
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.0" (15 cm)

Temperature Range

