

VT65MLBIFRADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in medical all-freezer with lock, capable of -25° C operation; door accepts panels

Highlights:

- 32 inch height fits under lower ADA compliant counters
- Flexible design allows built-in or freestanding use
- Factory installed lock provides security you can count on

Product Features:

ADA Compliant	32 inch height is designed to fit under ADA compliant counters
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry
Fully finished white cabinet	Allows the unit to be used freestanding
Factory installed lock	Keep contents secure with a front lock on the door
Stainless steel door frame	Two-piece "U"-shaped frame accepts slide-in panels to create a customized look
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost operation	Static cooling system for improved temperature stability
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened
Digital thermostat	Electronic controls located in the front kickplate for easy and intuitive temperature management

VT65MLBIFRADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101043432
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.0" (15 cm)
Temperature Range	-12°C to -25°C

