accuc@ld

VT65MLBIMEDADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in undercounter all-freezer capable of -25° C operation; includes audible alarm, lock, and hospital grade plug

Highlights:

Flexible design allows built-in or freestanding use in 24" wide spaces

32" height for use in ADA compliant settings

-25° C operation for safe storage of temperature sensitive materials

Product Features:

| ADA compliant | 32" high to fit under lower ADA compliant counters | |
|-------------------------------------------|----------------------------------------------------------------------------------------------------|--|
| Built-in capable | Make the best use of space by installing your appliance under the counter | |
| Hospital grade cord with 'green dot' plug | Secure three-pronged cord for added unit safety | |
| Factory installed lock | Keyed lock for secure interior | |
| -25°C capable | Low temperature capability ideal for certain sensitive items | |
| High temperature alarm | Warns of temperature fluctuations and includes an external temperature readout on the door | |
| Manual defrost | Efficient performance with reliable temperature stability | |
| Three removable storage baskets | Conveniently organize your items while keeping the temperature stable when the door is opened | |
| Access port | Unit comes with a factory installed probe hole for users to connect their own monitoring equipment | |





accuc@ld

VT65MLBIMEDADA Specifications:

| Overview | | | |
|-------------------------------|--------------------|--|--|
| Nominal Height | 32.0" (81 cm) | | |
| | | | |
| Height of Cabinet | 32.0" (81 cm) | | |
| Height to Hinge Cap | 32.25" (82 cm) | | |
| Nominal Width | 24.0" (61 cm) | | |
| Width | 23.63" (60 cm) | | |
| Nominal Depth | 24.0" (61 cm) | | |
| Depth | 23.5" (60 cm) | | |
| Depth with Handle | 24.25" (62 cm) | | |
| Depth with door at 90° | 45.13" (115 cm) | | |
| Capacity | 3.2 cu.ft. (91 L) | | |
| Defrost Type | Manual | | |
| Door | White | | |
| Cabinet | White | | |
| US Electrical Safety | UL | | |
| Canadian Electrical Safety | ULC | | |
| Amps | 1.3 | | |
| Voltage/Frequency | 115 V AC/60 Hz | | |
| Weight | 105.0 lbs. (48 kg) | | |
| Parts & Labor Warranty | 1 Year | | |
| Compressor Warranty | 5 Years | | |
| UPC | 761101044705 | | |
| Freezer | | | |
| Door Swing | RHD | | |
| Reversible | Factory Reversible | | |
| Interior Height | 24.25" (62 cm) | | |
| Interior Width | 17.75" (45 cm) | | |
| Interior Depth | 16.5" (42 cm) | | |
| Thermostat Type | Digital | | |
| Fan Type | Exterior | | |
| Refrigerant Type | R134a | | |
| Refrigerant Amount | 2.7 oz. | | |
| High Side PSI | 235.0 | | |
| Low Side PSI | 70.0 | | |
| Interior Drawers | Yes | | |
| Drawers Qty | 3 | | |
| Compressor Step Height | 6.5" (17 cm) | | |
| Compressor Step Width | 17.5" (44 cm) | | |
| ,p | - (| | |

| Compressor Step Depth | 5.5" (14 cm) |
|-----------------------|----------------|
| Temperature Range | -12°C to -25°C |

