### accuc@ld

# CM4057SSHVADA



32.5" x 19.25" x 21.38" (H x W x D)

Commercially listed ADA compliant 20" wide freestanding refrigerator-freezer with stainless steel door, thin handle, and white cabinet

#### **Highlights:**

ETL-S listed for commercial use

32" height complies with ADA guidelines

Slim 20" width is ideal for any setting

#### **Product Features:**

ADA compliant	32" high meets ADA guidelines	
Commercially listed	ETL-S listed to NSF standards for commercial use	
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint	
Fully finished white cabinet	Allows the unit to be used freestanding	
Stainless steel wrapped door	Durable 304 grade wrapping	
Professional handle	Thin 14mm diameter on vertical stainless steel handle	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Manual defrost	Efficient performance with reliable temperature stability	
Adjustable shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup	



## accuc@ld

### **CM4057SSHVADA Specifications:**

Overview			
Height of Cabinet	32.0" (81 cm)		
Height to Hinge Cap	32.5" (83 cm)		
Width	19.25" (49 cm)		
Depth	21.38" (54 cm)		
Depth with door at 90°	39.5" (100 cm)		
Capacity	4.1 cu.ft. (116 L)		
Defrost Type	Manual		
Door	Stainless Steel		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Energy Usage/Year	339.0kWh/year		
Amps	1.4		
Voltage/Frequency	115 V AC/60 Hz		
Weight	64.0 lbs. (29 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101029313		
Refrigerator-Freezer			
Door Swing	RHD		
Reversible	Factory Reversible		
Adjustable Shelves	Yes		
Crisper Qty	1		
Crisper Finish	Transparent		
Crisper Cover	Glass		
Interior Light	Yes		
Refrigerator - Interior Height	28.75" (73 cm)		
Refrigerator - Interior Width	15.75" (40 cm)		
Refrigerator - Interior Depth	17.75" (45 cm)		
Refrigerator - Shelf Type	Wire		
Refrigerator - Shelf Qty	2		
Thermostat Type	Dial		
Refrigerant Type	R134a		

High Side PSI	205.0
Low Side PSI	103.0
Level Legs	2
Wheels	2



