

CM405BI7FR



34" x 19.25" x 21.38" (H x W x D)

Commercially listed 20" wide built-in undercounter refrigerator-freezer in white with stainless steel door frame for slide-in custom panels

Highlights:

- ETL-S listed for commercial use
- Flexible design allows built-in or freestanding use
- Slim 20" width is ideal for any setting

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Built-in capable	Make the best use of space by installing your appliance under the counter
Fully finished white cabinet	Allows the unit to be used freestanding
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Stainless steel door frame	Two-piece "U"-shaped door frame accepts slide-in custom panels (panel size: 19 1/4" W x 31 1/4" H)
Reversible door	User reversible door swing
Manual defrost	Efficient performance with reliable temperature stability
Adjustable shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup

CM405BI7FR Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Height to Hinge Cap	34.0" (86 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	4.1 cu.ft. (116 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	339.0kWh/year
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	64.0 lbs. (29 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101034560
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Yes
Adjustable Shelves	Yes
Crisper Qty	1
Crisper Finish	Transparent
Crisper Cover	Glass
Interior Light	Yes
Refrigerator - Interior Height	28.75" (73 cm)
Refrigerator - Interior Width	15.75" (40 cm)
Refrigerator - Interior Depth	17.75" (45 cm)
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.75 oz.
High Side PSI	205.0
Low Side PSI	103.0

Level Legs	2
Wheels	2

