accuc@ld

FF67DPLADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant commercial all-refrigerator for freestanding general purpose use, auto defrost with diamond plate door, towel bar handle, and white cabinet

Highlights:

32" height for use in ADA compliant settings

Commercially approved for use in foodservice establishments

Full 5.5 cu.ft. capacity inside a convenient 24" footprint

Product Features:

Commercially approved	ETL-S listed to NSF-7 commercial standards	
ADA compliant	32" height for use in settings complying with ADA guidelines for lower counter height	
Slim counter height dimensions	Ideal 24" footprint offers full 5.5 cu.ft. storage capacity in a slim fit	
Fully finished white cabinet	Allows the unit to be used freestanding	
Diamond plate finish on door	Textured diamond plate finish in wrapped aluminum creates a unique industrial look	
Professional towel bar handle	Curved handle in polished stainless steel completes the look	
Automatic defrost	Reduced maintenance with auto defrost system	
Hidden evaporator	Cold wall design with hidden evaporator and seamless interior	
One piece interior liner	Easy clean-up with a seamless liner that won't hold a mess in hidden crevices	





accuc@ld

FF67DPLADA Specifications:

Height of Cabinet 32.0" (81 cm) Height to Hinge Cap 32.25" (82 cm) Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 26.38" (67 cm) Depth with door at 90° 46.13" (117 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety ULC Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg) Shipping Weight 105.0 lbs. (48 kg)		
Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 26.38" (67 cm) Depth with door at 90° 46.13" (117 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Depth 23.5" (60 cm) Depth with Handle 26.38" (67 cm) Depth with door at 90° 46.13" (117 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Depth with Handle 26.38" (67 cm) Depth with door at 90° 46.13" (117 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Depth with door at 90° 46.13" (117 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
US Electrical Safety Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency Weight 100.0 lbs. (45 kg)		
Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Weight 100.0 lbs. (45 kg)		
Shipping Weight 105.0 lbs. (48 kg)		
Parts & Labor Warranty 1 Year		
Compressor Warranty 5 Years		
UPC 761101040387		
Refrigerator Features		
Door Swing RHD		
Reversible Factory Reversible		
Crisper Qty 1		
Crisper Finish Opaque		
Crisper Cover Glass		
Shelf Type Wire		
Shelf Qty 3		
Full Door Shelf Qty 3		
Adjustable Shelves Yes		
Thermostat Type Dial		
Fan Type Exterior		
Refrigerant Type R134a		
Refrigerant Amount 1.8oz.		
High Side PSI 285.0		
Low Side PSI 70.0		
Level Legs Qty 4		

Interior Light	Yes
Dimensions	
Interior Height	27.75" (70 cm)
Interior Width	20.0" (51 cm)
Interior Depth	17.5" (44 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	6.0" (15 cm)

