accuc@ld

FF7DPL



33.25" x 23.63" x 23.5" (H x W x D)

Commercially listed freestanding all-refrigerator for general purpose use, auto defrost w/diamond plate wrapped door, towel bar handle, and white cabinet

Highlights:

Commercially approved for use in foodservice establishments

Automatic defrost minimizes user maintenance

Full 5.5 cu.ft. capacity inside a convenient 24" footprint

Product Features:

Commercially approved	ETL-S Approved to ANSI-NSF Standard 7	
Fully finished cabinet	Allows the refrigerator to be used as a freestanding model	
Diamond plate finish on door	Textured diamond plate finish in wrapped aluminum creates a unique industrial look	
Professional towel bar handle	Curved handle in polished stainless steel completes the look	
Automatic defrost	Reduced user maintenance with automatic defrost	
Adjustable shelves	Rearrange your refrigerator space to accommodate all shapes and sizes or remove shelves for a simple clean-up	
Hidden evaporator	Cold wall design with hidden evaporator and seamless interior	
One piece interior liner	Enjoy easy clean-up with a seamless liner that won't hold a mess in hidden crevices	
Deep shelf space	Interior accommodates large trays up to 19 1/2" x 15 1/2"	



accuc@ld

FF7DPL Specifications:

Height of Cabinet 32.63" (83 cm) Height to Hinge Cap 33.25" (84 cm) Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety ULC Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg) Parts & Labor Warranty 1 Year			
Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Defrost Type Automatic Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Door Diamond Plate Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
US Electrical Safety Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)			
Weight 100.0 lbs. (45 kg)			
Parts & Labor Warrantv 1 Year			
Compressor Warranty 5 Years			
UPC 761101052717			
Refrigerator Features			
Door Swing RHD			
Reversible Factory Reversible			
Shelf Type Wire			
Shelf Qty 3			
Adjustable Shelves Yes			
Thermostat Type Dial			
Fan Type Exterior			
Refrigerant Type R134a			
Refrigerant Amount 1.8oz.			
High Side PSI 285.0			
Low Side PSI 70.0			
Level Legs Qty 2			
Interior Light Yes			
Dimensions			
Interior Height 27.75" (70 cm)			
Interior Width 20.0" (51 cm)			
Interior Depth 17.5" (44 cm)			

Compressor Step Height	7.0" (18 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	6.0" (15 cm)

