

FS24LPLUS



20" x 18.5" x 17.63" (H x W x D)

Compact all-freezer, manual defrost with a lock and thermometer

Highlights:

Compact size is ideal for countertop use

Factory installed lock provides security you can count on

Thermometer provides NIST calibrated external readout of current and high/low temperature

Product Features:

Compact dimensions	Ideal size for use on top of counters
Factory installed lock	Keyed security for a secure interior
NIST calibrated thermometer	Thermometer provides external readout of current and high/low temperatures
Manual defrost	Static cooling system for reduced temperature fluctuations
-20° capable	Low temperature capability ideal for certain sensitive items
Removable shelf	Includes one wire shelf for easier storage
One-piece interior liner	Seamless interior for easier cleanup
Adjustable thermostat	Dial thermostat located inside for easy temperature management
Flat door liner	Designed to comply with CDC guidelines

FS24LPLUS Specifications:

Overview	
Height of Cabinet	19.63" (50 cm)
Height to Hinge Cap	20.0" (51 cm)
Width	18.5" (47 cm)
Depth	17.63" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	35.0 lbs. (16 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101047850
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.38" (37 cm)
Interior Width	13.5" (34 cm)
Interior Depth	13.25" (34 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.5 oz.
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	13.5" (34 cm)
Compressor Step Depth	6.0" (15 cm)

