



# SBC635MBIIFTWIN



33.5" x 24" x 25.88" (H x W x D)

Built-in residential beer dispenser, auto defrost with digital thermostat, dual tap system, panel-ready door, and black cabinet

### Highlights:

- Dual tap system allows you to serve beer from two 1/6 kegs
- Designed for built-in installation under the counter
- Customizable door front accepts full overlay panels for a seamless look that can blend into cabinetry

### Product Features:

|                              |   |
|------------------------------|---|
| Full-sized beer dispenser    | Large 5.6 cu.ft. interior can accept a full half barrel keg, two 1/6 barrel kegs, or a pony keg   |
| Built-in capable             | Front-breathing design lets you make the best use of space by installing your appliance under the counter   |
| Dual tap system              | Twin taps let you serve two different types of beer from two 1/6 sized (sixtel) kegs  |
| Tap Kit                      | Includes a regulator, draft arm, Sankey American tap, and connection hardware   |
| Panel-ready door             | Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the door or blend it into your cabinetry design (panel dimensions: 23 3/4" W x 30 13/16" H and at least 3/4" thick; maximum weight: 10 lbs.) |
| Digital thermostat           | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit   |
| Ideal beer temperature       | Operates between 33° and 50°F to keep a variety of beers stored at just the right serving temperature   |
| Automatic defrost            | Reduced user maintenance with auto defrost operation  |
| Fully finished black cabinet | Allows the beer dispenser to be used freestanding   |



## SBC635MBIIFTWIN Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 33.5" (85 cm)      |
| Width                      | 24.0" (61 cm)      |
| Width with Door Open       | 25.25" (64 cm)     |
| Depth                      | 25.88" (66 cm)     |
| Depth with door at 90°     | 47.5" (121 cm)     |
| Capacity                   | 5.6 cu.ft. (159 L) |
| Defrost Type               | Automatic          |
| Door                       | Panel-Ready        |
| Cabinet                    | Black              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Energy Usage/Year          | 310.0kWh/year      |
| Amps                       | 0.86               |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 100.0 lbs. (45 kg) |
| Shipping Weight            | 134.0 lbs. (61 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101046082       |
| Kegerator                  |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Tap Kit                    | Yes                |
| Number of Taps             | 2                  |
| Thermostat Type            | Digital            |
| Fan Type                   | Exterior           |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 1.13 oz.           |
| High Side PSI              | 250.0              |
| Low Side PSI               | 110.0              |
| Inter Height               | 28.0" (71 cm)      |
| Interior Width             | 20.5" (52 cm)      |
| Interior Depth             | 19.0" (48 cm)      |
| Compressor Step Height     | 8.25" (21 cm)      |
| Level Legs Qty             | 4                  |
| Wheel Qty                  | 4                  |
| Temperature Range          | 33° to 50° F       |

