

# CM411L7FR



34" x 19.25" x 21.38" (H x W x D)

Commercially listed 20" wide freestanding refrigerator-freezer with a lock, custom door for slide-in panels and white exterior

### Highlights:

ETL-S listed for commercial use

Slim 20" width is ideal for any setting

Factory installed lock provides security you can count on

### Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Fully finished white cabinet	Allows the unit to be used freestanding
Stainless steel door frame	Two-piece "U"-shaped door frame accepts slide-in custom panels (panel size: 19 1/4" W x 31 1/4" H)
Reversible door	User reversible door swing
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Manual defrost	Efficient performance with reliable temperature stability
Adjustable shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup
Crisper drawer	Get the longest life and best taste out of produce by storing greens in a bottom crisper

## CM411L7FR Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Height to Hinge Cap	34.0" (86 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	4.1 cu.ft. (116 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	64.0 lbs. (29 kg)
Shipping Weight	85.0 lbs. (39 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101031026
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Yes
Adjustable Shelves	Yes
Crisper Qty	1
Crisper Finish	Transparent
Crisper Cover	Glass
Interior Light	Yes
Refrigerator - Interior Height	28.75" (73 cm)
Refrigerator - Interior Width	15.75" (40 cm)
Refrigerator - Interior Depth	17.75" (45 cm)
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.75 oz.
High Side PSI	205.0
Low Side PSI	103.0

Level Legs	2
Wheels	2

