

SCF1312DTPDC



45.25" x 50" x 24" (H x W x D)

50" wide dipping cabinet with polycarbonate sneezeguard

Highlights:

Commercially listed to NSF-7 standards and CalCode compliant

Fully assembled dipping cabinet with durable polycarbonate sneezeguard

Digital thermostat for easy temperature control

Product Features:

| Commercially listed | ETL-S listed to NSF-7 Standards for use in commercial establishments | |
|-------------------------------|---|--|
| Digital thermostat | Electronic controls for more precise temperature management | |
| Sneezeguard | Durable polycarbonate sneezeguard with stainless steel support | |
| Casters | Heavy duty casters for smooth mobility | |
| Manual defrost | Static cooling system for improved temperature stability; temperature range: 0 to 5°F | |
| Factory installed lock | Keyed lock for secure interior | |
| Fan-cooled compressor | Ensures an evenly cooled interior | |
| Hammered aluminum interior | Durable and easy to clean with a 19 5/8" height to accommodate stacked items | |
| Choice of storage accessories | Specify gelato pan holders or tub holders upon order | |







SCF1312DTPDC Specifications:

| Overview | | |
|-------------------------------|---------------------|--|
| Height of Cabinet | 45.25" (115 cm) | |
| Width | 50.0" (127 cm) | |
| Depth | 24.0" (61 cm) | |
| Capacity | 13.0 cu.ft. (368 L) | |
| Defrost Type | Manual | |
| Door | Glass | |
| Cabinet | White | |
| US Electrical Safety | ETL | |
| Canadian Electrical Safety | ETL-C | |
| Sanitation | ETL-S | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Parts & Labor Warranty | 1 Year | |
| Compressor Warranty | 5 Years | |
| UPC | 761101047522 | |
| Freezer | | |
| Door Swing | Sliding | |
| Thermostat Type | Digital | |
| Wheels | 4 | |
| Temperature Range | 0º to 5°F | |

