

SP6DSSTBOS7THIN



33.25" x 23.75" x 25.5" (H x W x D)

Three-drawer commercial outdoor all-refrigerator in complete stainless steel with automatic defrost operation and sleek professional handles

Highlights:

ETL-S listed to NSF-7 commercial standards

Weatherproof construction ensures safe operation in the outdoors

Flexible design allows built-in or freestanding use

Product Features:

| Weatherproof design | Designed and constructed for durable use in the outdoors |
|---|---|
| Commercially approved | ETL-S listed to NSF standards and approved to UL-471 electrical standard for commercial use |
| Complete 304 grade stainless steel construction | Non-corrodible stainless steel lasts in any season |
| Built-in capable | Make the best use of space by installing your appliance under the counter and flush with other cabinets |
| Automatic defrost | Reduced maintenance with auto defrost system |
| Three slide-out drawers | Smoothly gliding stainless steel drawers for easy use |
| Professional handles | Thin (14mm diameter) stainless steel handles for a sleek look that matches many popular styles of cabinetry |
| Adjustable thermostat | Dial thermostat for easy temperature management |
| Magnetic gaskets | Ensures the drawers are tightly sealed to protect stored items |

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com





SP6DSSTBOS7THIN Specifications:

| Height of Cabinet33.25" (84 cm)Width23.75" (60 cm)Depth25.5" (65 cm)Capacity3.1 cu.ft. (88 L)Defrost TypeAutomaticDoorStainless SteelCabinetStainless SteelUS Electrical SafetyETL-CCanadian ElectricalETL-C |
|--|
| Depth25.5" (65 cm)Capacity3.1 cu.ft. (88 L)Defrost TypeAutomaticDoorStainless SteelCabinetStainless SteelUS Electrical SafetyETL |
| Capacity3.1 cu.ft. (88 L)Defrost TypeAutomaticDoorStainless SteelCabinetStainless SteelUS Electrical SafetyETL |
| Defrost TypeAutomaticDoorStainless SteelCabinetStainless SteelUS Electrical SafetyETL |
| DoorStainless SteelCabinetStainless SteelUS Electrical SafetyETL |
| Cabinet Stainless Steel US Electrical Safety ETL |
| US Electrical Safety ETL |
| |
| Canadian Electrical |
| Safety |
| Sanitation ETL-S |
| Amps 1.3 |
| Voltage/Frequency 115 V AC/60 Hz |
| Weight 120.0 lbs. (54 kg) |
| Parts & Labor Warranty 1 Year |
| Compressor Warranty 5 Years |
| UPC 761101038643 |
| Refrigerator Features |
| Thermostat Type Dial |
| Fan Type Exterior |
| Refrigerant Type R134a |
| Refrigerant Amount 1.8oz. |
| High Side PSI 285.0 |
| Low Side PSI 70.0 |
| Drawer Dimensions |
| Interior Height 1 6.25" (16 cm) |
| Interior Width 1 18.63" (47 cm) |
| Interior Depth 1 11.5" (29 cm) |
| Interior Height 2 6.25" (16 cm) |
| Interior Width 2 18.63" (47 cm) |
| Interior Depth 2 16.0" (41 cm) |
| Interior Height 3 6.25" (16 cm) |
| |
| Interior Width 3 17.25" (44 cm) |
| Interior Width 3 17.25" (44 cm) Interior Depth 3 16.0" (41 cm) |
| |
| Interior Depth 3 16.0" (41 cm) |
| Interior Depth 3 16.0" (41 cm) Dimensions |



