accuc@ld

FS30L7



24.63" x 18.5" x 17.75" (H x W x D)

Compact commercially listed manual defrost all-freezer with lock and reversible door

Highlights:

Commercially listed to NSF-7 standards

Compact size is ideal for countertop use

Factory installed lock provides added security

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments	
Compact dimensions	Sized for easy use on top of counters	
Fully finished cabinet	Allows the unit to be used freestanding	
Manual defrost	Static cooling system for improved temperature stability	
Adjustable thermostat	Dial thermostat located inside the unit	
Factory installed lock	Keyed lock for a secure interior	
Reversible door	User-reversible door swing allows for more flexibility in placing the unit	
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup	
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials	





accuc@ld

FS30L7 Specifications:

Overview		
Nominal Height	25.0" (64 cm)	
Height of Cabinet	24.5" (62 cm)	
Height to Hinge Cap	24.63" (63 cm)	
Nominal Width	19.0" (48 cm)	
Width	18.5" (47 cm)	
Nominal Depth	18.0" (46 cm)	
Depth	17.75" (45 cm)	
Depth with door at 90°	34.5" (88 cm)	
Capacity	1.8 cu.ft. (51 L)	
Defrost Type	Manual	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	0.8	
Voltage/Frequency	115 V AC/60 Hz	
Weight	43.0 lbs. (20 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101053219	
Freezer		
Door Swing	RHD	
Reversible	Yes	
Interior Height	18.63" (47 cm)	
Interior Width	13.38" (34 cm)	
Interior Depth	13.0" (33 cm)	
Shelf Type	Wire	
Shelf Qty	2	
Thermostat Type	Dial	
Refrigerant Type	R600a	
Refrigerant Amount	0.8 oz.	
Level Legs	2	
Compressor Step Height	8.0" (20 cm)	
Compressor Step Width	13.38" (34 cm)	
Compressor Step Depth	5.75" (15 cm)	
Sound Level	33.3 dB	

