



FS30L7PLUS



24.63" x 18.5" x 17.75" (H x W x D)

Compact commercially listed manual defrost all-freezer with external thermometer and lock

Highlights:

Commercially listed to NSF-7 standards

Compact size is ideal for countertop use

Thermometer provides NIST calibrated external readout of current and high/low temperature

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Compact dimensions	Sized for easy use on top of counters
Manual defrost	Static cooling system for improved temperature stability
-20°C capable	Low temperature capability ideal for certain sensitive items
Factory installed lock	Keyed lock for a secure interior
NIST calibrated thermometer	Thermometer provides external readout of current and high/low temperatures
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup
Adjustable thermostat	Dial thermostat located inside the unit
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials

FS30L7PLUS Specifications:

Overview	
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.63" (63 cm)
Width	18.5" (47 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	50.0 lbs. (23 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)

