

SBC635M7SSTBTWIN



33.5" x 23.63" x 25.5" (H x W x D)

Freestanding commercially listed dual tap beer dispenser, auto defrost with digital thermostat, stainless steel door, towel bar handle, and black cabinet

Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Dual tap system allows you to serve beer from two 1/6 kegs

Includes everything you need to pour the perfect draft

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Full-sized beer dispenser	Large 5.6 cu.ft. interior accepts half, quarter, and mini kegs
Dual tap system	Twin taps let you serve two different types of beer from two 1/6 sized (sixtel) kegs
Tap Kit	Includes a regulator, draft arm, Sankey American tap, and connection hardware
Automatic defrost	Reduced user maintenance with auto defrost operation
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit
Ideal beer temperature	Operates between 33° and 50°F to keep a variety of beers stored at just the right serving temperature
Fully finished black cabinet	Allows the beer dispenser to be used freestanding
Stainless steel wrapped door	Solid construction in 304 grade stainless steel

SBC635M7SSTBTWIN Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Width with Door Open	25.0" (64 cm)
Depth	25.5" (65 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	5.6 cu.ft. (159 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	0.86
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101051598
Kegeerator	
Door Swing	RHD
Reversible	Factory Reversible
Tap Kit	Yes
Height with Tap	49.0" (124 cm)
Number of Taps	2
Thermostat Type	Digital
Refrigerant	R600a
Refrigerant Amount	1.13 oz.
High Side PSI	250.0
Low Side PSI	110.0
Inter Height	28.0" (71 cm)
Interior Width	20.5" (52 cm)
Interior Depth	19.0" (48 cm)
Compressor Step Height	8.25" (21 cm)
Wheel Qty	4
Temperature Range	33° to 50° F

