

SBC635M7SSHH



49" x 23.63" x 25.5" (H x W x D)

Freestanding commercially listed beer dispenser, auto defrost with digital thermostat, stainless steel door, horizontal handle, and black cabinet

Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Full-sized capacity to hold half, quarter, 1/6 or mini kegs

Includes everything you need to pour the perfect draft

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Full-sized beer dispenser	Large 5.6 cu.ft. interior accepts half, quarter, and mini kegs
Tap Kit	Includes a regulator, draft arm, Sankey American tap, and connection hardware
Automatic defrost	Reduced user maintenance with auto defrost operation
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit
Ideal beer temperature	Operates between 33° and 50°F to keep a variety of beers stored at just the right serving temperature
Fully finished black cabinet	Allows the beer dispenser to be used freestanding
Stainless steel wrapped door	Solid construction in 304 grade stainless steel
Professional handle	Brushed stainless steel handle with a thin 14mm diameter is mounted horizontally across the door for a sleek look



SBC635M7SSHH Specifications:

Overview	
Height of Cabinet	49.0" (124 cm)
Width	23.63" (60 cm)
Width with Door Open	25.0" (64 cm)
Depth	25.5" (65 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	5.6 cu.ft. (159 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	0.86
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Shipping Weight	142.0 lbs. (64 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101051543
Kegerator	
Door Swing	RHD
Reversible	Yes
Tap Kit	Yes
Number of Taps	1
Thermostat Type	Digital
Refrigerant	R600a
Refrigerant Amount	1.13 oz.
High Side PSI	250.0
Low Side PSI	110.0
Inter Height	28.0" (71 cm)
Interior Width	20.5" (52 cm)
Interior Depth	19.0" (48 cm)
Compressor Step Height	8.25" (21 cm)
Wheel Qty	4
Temperature Range	33° to 50° F

