SUMMIT

BIM25



25.25" x 15" x 18.25" (H x W x D)

Compact manual defrost icemaker for built-in use under counters

Highlights:

Compact size for easy placement

Flexible design allows built-in or freestanding use

Professional exterior for modern look

Product Features:

Built-in capable	Make the best use of space by installing your icemaker under the counter and flush with other cabinets	
Mid-sized capacity	Produces and stores up to 12 pounds of ice per day cycle	
Insulated storage bin	Ice stays solid longer in this cold-protected bin	
Manual defrost	Side drain included for easier cleanup	
Ice scoop included	Large plastic ice scoop included for your convenience	
Fully finished cabinet	Allows the icemaker to be used freestanding	
100% CFC free	Environmentally friendly design without ozone-damaging chemicals	



SUMMIT

BIM25 Specifications:

Overview	
Height of Cabinet	24.75" (63 cm)
Height to Hinge Cap	25.25" (64 cm)
Width	15.0" (38 cm)
Depth	18.25" (46 cm)
Depth with door at 90°	31.75" (81 cm)
Capacity	1.0 cu.ft. (28 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.5
Voltage/Frequency	115 V AC/60 Hz
Weight	50.0 lbs. (23 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101059273
Icemaker	
Door Swing	RHD
Reversible	Factory Reversible
Daily Ice Production	12.0 lbs. (5 kg)
Ice Storage Capacity	12.0 lbs. (5 kg)
Ice Shape	Crescent
Number of Ice Cube Sizes	1
Refrigerant Type	R600a
Refrigerant Amount	0.63 oz.
High Side PSI	250.0
Low Side PSI	110.0
Interior Height	11.5" (29 cm)
Interior Width	10.0" (25 cm)
Interior Depth	12.63" (32 cm)
Level Legs	2



