

FF511LBIMED2ADA



32.25" x 19.25" x 22.63" (H x W x D)

Built-in undercounter ADA compliant auto defrost medical/scientific all-refrigerator with front control panel equipped with a digital thermostat and NIST calibrated thermometer/alarm; includes front lock, hospital grade cord, and internal fan

Highlights:

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

Flexible design allows built-in or freestanding use in 20" wide spaces

Product Features:

| | |
|-------------------------------------|--|
| Reliable temperature stability | Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions |
| Built-in capable | Front-breathing system allows the unit to be used built-in |
| ADA compliant | Sized at 32 1/4" high to allow installation under lower ADA compliant counters |
| Digital thermostat | Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range |
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button |
| Buffered temperature probe | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines |
| Factory installed lock | Keyed lock conveniently located towards the top of the door for added security (2 keys included) |
| Automatic defrost | Reduced maintenance with auto defrost system |

FF511LBIMED2ADA Specifications:

| Overview | |
|----------------------------|-----------------------|
| Height of Cabinet | 32.25" (82 cm) |
| Width | 19.25" (49 cm) |
| Depth | 22.63" (57 cm) |
| Depth with Handle | 24.63" (63 cm) |
| Depth with door at 90° | 40.75" (104 cm) |
| Capacity | 4.1 cu.ft. (116 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.4 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 70.0 lbs. (32 kg) |
| Shipping Weight | 75.0 lbs. (34 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101056487 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Shelf Type | Wire |
| Shelf Qty | 3 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior and Exterior |
| Refrigerant Type | R134a |
| Refrigerant Amount | 1.75oz. |
| High Side PSI | 205.0 |
| Low Side PSI | 103.0 |
| Level Legs Qty | 4 |
| Interior Light | Yes |
| Temperature Range | 2° to 8°C |
| Dimensions | |
| Interior Height | 28.5" (72 cm) |
| Interior Width | 15.75" (40 cm) |
| Interior Depth | 17.25" (44 cm) |

| | |
|------------------------|----------------|
| Compressor Step Height | 8.0" (20 cm) |
| Compressor Step Width | 15.75" (40 cm) |
| Compressor Step Depth | 6.5" (17 cm) |

