accucold

FFAR10MED2



56.75" x 23.63" x 23.5" (H x W x D)

10.1 cu.ft. upright auto defrost medical/scientific allrefrigerator with digital thermostat and NIST calibrated thermometer/alarm; includes front lock, hospital grade cord, and internal fan

Highlights:

Specially designed and featured to meet the CDC, VFC and VFA's guidelines for safe vaccine storage

High temperature alarm includes NIST calibrated external temperature readout (NIST certificate included)

Assembled in the USA from domestic and imported components

Product Features:

Reliable temperature stability	Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions	
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines	
Factory installed lock	Keyed lock conveniently located towards the top of the door for added security (2 keys included)	
Automatic defrost	Reduced maintenance with auto defrost system	
Internal fan	Fan-forced cooling ensures the unit is evenly cooled from top to bottom	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety in high traffic areas	
SUMMIT APPLIANCE DIVISION, FELIX STORO 770 Garrison Avenue Bronx, NY 10474 USA TEL 718		

accucold

FFAR10MED2 Specifications:

Overview			
Nominal Height	57.0" (145 cm)		
Height of Cabinet	56.75" (144 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.63" (60 cm)		
Nominal Depth	24.0" (61 cm)		
Depth	23.5" (60 cm)		
Depth with Handle	24.75" (63 cm)		
Depth with door at 90°	45.5" (116 cm)		
Capacity	10.1 cu.ft. (286 L)		
Defrost Type	Automatic		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Other Energy Info	120 Volts / 60 Hz.		
Amps	1.5		
Weight	140.0 lbs. (64 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101056579		
Refrigerator Features			
Door Swing	RHD		
Reversible	Factory Reversible		
Shelf Type	Wire		
Shelf Qty	4		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior		
Refrigerant Type	R134a		
Refrigerant Amount	3.0oz.		
High Side PSI	285.0		
Low Side PSI	70.0		
Level Legs Qty	2		
Interior Light	Yes		
Temperature Range	2ºC to 8ºC		
Dimensions			
Interior Height	48.25" (123 cm)		

Interior Width	20.5" (52 cm)
Interior Depth	17.75" (45 cm)
Compressor Step Height	6.25" (16 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.5" (14 cm)



