accuc@ld

FF28LWHMED2



26.63" x 18.5" x 17.75" (H x W x D)

Compact auto defrost medical/scientific all-refrigerator with digital thermostat, NIST calibrated thermometer/alarm, front lock, hospital grade cord, and internal fan

Highlights:

Specially designed and featured to meet the CDC, VFC and VFA's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Assembled in the USA from domestic and imported components

Product Features:


| Reliable temperature stability | Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions | |
|-------------------------------------|---|--|
| Digital thermostat | Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience | |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range | |
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button | |
| Buffered temperature probe | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines | |
| Factory installed lock | Keyed lock for added security, with two keys included | |
| Automatic defrost | Reduced maintenance with auto defrost system | |
| Internal fan | Fan-forced cooling ensures the unit is evenly cooled from top to bottom | |
| Flat door liner | Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials | |

accuc@ld

FF28LWHMED2 Specifications:

| Overview | | | |
|-------------------------------|--------------------|--|--|
| Nominal Height | 27.0" (69 cm) | | |
| Height of Cabinet | 26.63" (68 cm) | | |
| Nominal Width | 19.0" (48 cm) | | |
| Width | 18.5" (47 cm) | | |
| Nominal Depth | 18.0" (46 cm) | | |
| Depth | 17.75" (45 cm) | | |
| Depth with door at 90° | 34.5" (88 cm) | | |
| Capacity | 2.4 cu.ft. (68 L) | | |
| Defrost Type | Automatic | | |
| Door | White | | |
| Cabinet | White | | |
| US Electrical Safety | ETL | | |
| Canadian Electrical Safety | ETL-C | | |
| Amps | 0.7 | | |
| Voltage/Frequency | 115 V AC/60 Hz | | |
| Weight | 45.0 lbs. (20 kg) | | |
| Parts & Labor Warranty | 2 Years | | |
| Compressor Warranty | 5 Years | | |
| UPC | 761101056456 | | |
| Refrigerator Features | | | |
| Door Swing | RHD | | |
| Reversible | Factory Reversible | | |
| Shelf Type | Wire | | |
| Shelf Qty | 2 | | |
| Thermostat Type | Digital | | |
| Fan Type | Interior | | |
| Refrigerant Type | R600a | | |
| Refrigerant Amount | 0.7oz. | | |
| High Side PSI | 120.0 | | |
| Low Side PSI | 70.0 | | |
| Level Legs Qty | 2 | | |
| Temperature Range | 2 to 8°C | | |
| Dimensions | | | |
| Interior Height | 20.5" (52 cm) | | |
| Interior Width | 15.5" (39 cm) | | |
| Interior Depth | 13.5" (34 cm) | | |
| | | | |

| Compressor Step Width | 15.5" (39 cm) |
|-----------------------|---------------|
| Compressor Step Depth | 5.5" (14 cm) |





ELEC. CORD-