

# FF28LWHPLUS2



24.88" x 18.5" x 17.75" (H x W x D)

Compact all-refrigerator with automatic defrost, digital thermostat, internal fan, NIST calibrated thermometer, and lock; replaces FF28LWHPLUS

### Highlights:

- NIST calibrated thermometer displays the current and high/low temperature to the nearest tenth of a degree
- Factory installed lock provides security you can count on
- Internal fan-forced cooling for more temperature stability

### Product Features:

|                                     |   |
|-------------------------------------|---|
| Automatic defrost                   | Reduced maintenance with auto defrost system  |
| Factory installed lock              | Keyed lock for a secure interior  |
| NIST calibrated temperature display | Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button |
| Buffered temperature probe          | Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of refrigerator air temperature  |
| Digital thermostat                  | Electronic controls ensure easy and intuitive temperature management  |
| Internal fan                        | Fan-forced cooling ensures the unit is evenly cooled from top to bottom   |
| Flat door liner                     | Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials  |
| Wire shelving                       | Helps to ensure improved air circulation, with a full-width fixed wire shelf and a removable half shelf included  |
| Compact dimensions                  | Ideal size for use on top of counters   |

## FF28LWHPLUS2 Specifications:

| Overview                   |                       |
|----------------------------|-----------------------|
| Nominal Height             | 25.0" (64 cm)         |
| Height of Cabinet          | 24.5" (62 cm)         |
| Height to Hinge Cap        | 24.88" (63 cm)        |
| Nominal Width              | 19.0" (48 cm)         |
| Width                      | 18.5" (47 cm)         |
| Nominal Depth              | 18.0" (46 cm)         |
| Depth                      | 17.75" (45 cm)        |
| Depth with door at 90°     | 34.5" (88 cm)         |
| Capacity                   | 2.4 cu.ft. (68 L)     |
| Defrost Type               | Automatic             |
| Door                       | White                 |
| Cabinet                    | White                 |
| US Electrical Safety       | ETL                   |
| Canadian Electrical Safety | ETL-C                 |
| Amps                       | 0.7                   |
| Voltage/Frequency          | 115 V AC/60 Hz        |
| Weight                     | 36.0 lbs. (16 kg)     |
| Parts & Labor Warranty     | 1 Year                |
| Compressor Warranty        | 5 Years               |
| UPC                        | 761101057514          |
| Refrigerator Features      |                       |
| Door Swing                 | RHD                   |
| Reversible                 | Factory Reversible    |
| Shelf Type                 | Wire                  |
| Shelf Qty                  | 2                     |
| Thermostat Type            | Digital               |
| Fan Type                   | Interior              |
| Refrigerant Type           | R600a                 |
| Refrigerant Amount         | 0.7oz.                |
| High Side PSI              | 120.0                 |
| Low Side PSI               | 70.0                  |
| Level Legs Qty             | 2                     |
| Temperature Range          | 2 to 8°C / 36 to 46°F |
| Dimensions                 |                       |
| Interior Height            | 21.5" (55 cm)         |
| Interior Width             | 16.0" (41 cm)         |

|                        |               |
|------------------------|---------------|
| Interior Depth         | 13.5" (34 cm) |
| Compressor Step Height | 7.75" (20 cm) |
| Compressor Step Width  | 16.0" (41 cm) |
| Compressor Step Depth  | 5.0" (13 cm)  |

