accucold

FF511LBI7PLUS2



34" x 19.25" x 22.63" (H x W x D)

Commercially approved 20" wide built-in undercounter allrefrigerator, auto defrost with an internal fan, NIST calibatred thermometer, and lock

Highlights:

Flexible design allows built-in or freestanding use under counters in 20" wide spaces

NIST calibrated thermometer displays the current and high/low temperature to the nearest tenth of a degree

Digital thermostat ensures easy temperature management

Product Features:

Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint	
Commercially listed	ETL-S listed to NSF standards for commercial use	
Built-in capable	Make the best use of space by installing your appliance under the counter	
Fully finished white cabinet	Allows the unit to be used freestanding	
NIST calibrated temperature display	Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button	
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of refrigerator air temperature	
Digital thermostat	Electronic controls (located inside the refrigerator) ensure easy and intuitive temperature management	
Factory installed lock	Top-mounted for convenient security	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 \checkmark



www.summitappliance.com

accuceld

FF511LBI7PLUS2 Specifications:

Overview			
Height of Cabinet	33.5" (85 cm)		
Height to Hinge Cap	34.0" (86 cm)		
Width	19.25" (49 cm)		
Depth	22.63" (57 cm)		
Depth with Handle	23.0" (58 cm)		
Depth with door at 90°	39.5" (100 cm)		
Capacity	4.1 cu.ft. (116 L)		
Defrost Type	Automatic		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Amps	1.4		
Voltage/Frequency	115 V AC/60 Hz		
Weight	64.0 lbs. (29 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101057545		
Refrigerator Features			
Door Swing	RHD		
Reversible	Factory Reversible		
Height Adjustable	1		
Shelf Type	Wire		
Shelf Qty	3		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior and Exterior		
Refrigerant Type	R134a		
Refrigerant Amount	1.75oz.		
3			
High Side PSI	205.0		
	205.0		
High Side PSI			
High Side PSI Low Side PSI	103.0		
High Side PSI Low Side PSI Level Legs Qty	103.0		
High Side PSI Low Side PSI Level Legs Qty Interior Light	103.0 2 Yes		
High Side PSI Low Side PSI Level Legs Qty Interior Light Temperature Range	103.0 2 Yes		

Interior Width	15.75" (40 cm)
Interior Depth	18.0" (46 cm)
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.75" (17 cm)



