# accucold

# FF511LPLUS2



#### 34" x 19.25" x 21.38" (H x W x D)

20" wide counter height all-refrigerator, auto defrost with an internal fan, thermometer, and lock

#### **Highlights:**

NIST calibrated thermometer displays the current and high/low temperature to the nearest tenth of a degree

Slim 20" width is ideal for any setting

Digital thermostat ensures easy temperature management

### **Product Features:**

Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint	
NIST calibrated temperature display	Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button	
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of refrigerator air temperature	
Digital thermostat	Electronic controls (located inside the refrigerator) ensure easy and intuitive temperature management	
Automatic defrost	Reduced maintenance with auto defrost system	
Internal fan	Fan-forced cooling helps the unit stay evenly cooled from top to bottom	
Factory installed lock	Top-mounted for convenient security	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Adjustable shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 $\checkmark$ 



## accucold

## FF511LPLUS2 Specifications:

Overview		
Height of Cabinet	33.5" (85 cm)	
Height to Hinge Cap	34.0" (86 cm)	
Width	19.25" (49 cm)	
Depth	21.38" (54 cm)	
Depth with Handle	23.0" (58 cm)	
Depth with door at 90°	39.5" (100 cm)	
Capacity	4.1 cu.ft. (116 L)	
Defrost Type	Automatic	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	1.4	
Voltage/Frequency	115 V AC/60 Hz	
Weight	64.0 lbs. (29 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101057583	
Refrigerator Features		
Door Swing	RHD	
Reversible	Factory Reversible	
Shelf Type	Wire	
Shelf Qty	3	
Adjustable Shelves	Yes	
Thermostat Type	Digital	
Fan Type		
Таптурс	Interior	
Refrigerant Type	Interior R134a	
Refrigerant Type	R134a	
Refrigerant Type Refrigerant Amount	R134a 1.75oz.	
Refrigerant Type Refrigerant Amount High Side PSI	R134a 1.75oz. 205.0	
Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	R134a 1.75oz. 205.0 103.0	
Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty	R134a 1.75oz. 205.0 103.0 2	
Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light	R134a 1.75oz. 205.0 103.0 2 Yes	
Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light Temperature Range	R134a 1.75oz. 205.0 103.0 2 Yes	
Refrigerant Type   Refrigerant Amount   High Side PSI   Low Side PSI   Level Legs Qty   Interior Light   Temperature Range   Dimensions	R134a 1.75oz. 205.0 103.0 2 Yes 2 to 8ºC / 36 to 46ºF	
Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light Temperature Range <b>Dimensions</b> Interior Height	R134a 1.75oz. 205.0 103.0 2 Yes 2 to 8°C / 36 to 46°F 28.5" (72 cm)	

Compressor Step Height	8.0" (20 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.75" (17 cm)



