

# FS24L7PLUS2



20" x 18.5" x 17.63" (H x W x D)

Compact commercially listed all-freezer, manual defrost with a lock and NIST calibrated thermometer

## Highlights:

Commercially listed to NSF-7 standards

Compact size is ideal for countertop use

Factory installed lock provides security you can count on

## Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Compact dimensions	Ideal size for use on top of counters
Factory installed lock	Keyed security for a secure interior
-20° capable	Low temperature capability ideal for certain sensitive items
NIST calibrated thermometer	Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of freezer air temperature
One-piece interior liner	Seamless interior for easier cleanup
Manual defrost	Static cooling system for reduced temperature fluctuations
Wire shelving	Convenient storage with a wire design that helps ensure even temperature distribution

## FS24L7PLUS2 Specifications:

Overview	
Height of Cabinet	19.63" (50 cm)
Height to Hinge Cap	20.0" (51 cm)
Width	18.5" (47 cm)
Depth	17.63" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	35.0 lbs. (16 kg)
Shipping Weight	42.5 lbs. (19 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101057743
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.38" (37 cm)
Interior Width	13.5" (34 cm)
Interior Depth	13.25" (34 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.5 oz.
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	13.5" (34 cm)
Compressor Step Depth	6.0" (15 cm)

