accuc@ld

VT65MLBIPLUS2



33.5" x 23.63" x 23.5" (H x W x D)

24" wide all-freezer for built-in use, manual defrost with a NIST calibrated thermometer, lock, and -25°C capability

Highlights:

Flexible design allows built-in or freestanding use in 24 wide spaces

NIST calibrated thermometer displays the current and high/low temperature to the nearest tenth of a degree

-25° C operation for safe storage of temperature sensitive materials

Product Features:

Slim undercounter dimensions	Less than 24 wide to fit tight spaces	
Built-in capable	Make the best use of space by installing your appliance under the counter	
Factory installed lock	Keyed lock for secure interior	
Manual defrost	Efficient performance with reliable temperature stability	
-25°C capable	Low temperature capability ideal for certain sensitive items	
NIST calibrated temperature display	Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button	
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of freezer air temperature	
Pull-out drawers	Clear baskets for convenient and separated storage	
Matching refrigerator available	Pair with FF6LBIPLUS for a complete undercounter set	





accuc@ld

VT65MLBIPLUS2 Specifications:

Nominal Height 34.0" (86 cm) Height of Cabinet 33.5" (85 cm) Nominal Width 24.0" (61 cm) Width 23.63" (60 cm) Nominal Depth 24.0" (61 cm) Depth 23.5" (60 cm) Depth with Handle 25.13" (64 cm) Depth with door at 90° 46.13" (117 cm) Capacity 3.2 cu.ft. (91 L) Defrost Type Manual		
Nominal Width 24.0" (61 cm Width 23.63" (60 cm Nominal Depth 24.0" (61 cm Depth 23.5" (60 cm Depth with Handle 25.13" (64 cm Depth with door at 90° 46.13" (117 cm Capacity 3.2 cu.ft. (91 L		
Width 23.63" (60 cm Nominal Depth 24.0" (61 cm Depth 23.5" (60 cm Depth with Handle 25.13" (64 cm Depth with door at 90° 46.13" (117 cm Capacity 3.2 cu.ft. (91 L		
Nominal Depth 24.0" (61 cm Depth 23.5" (60 cm Depth with Handle 25.13" (64 cm Depth with door at 90° 46.13" (117 cm Capacity 3.2 cu.ft. (91 L		
Depth 23.5" (60 cm Depth with Handle 25.13" (64 cm Depth with door at 90° 46.13" (117 cm Capacity 3.2 cu.ft. (91 L		
Depth with Handle 25.13" (64 cm Depth with door at 90° 46.13" (117 cm Capacity 3.2 cu.ft. (91 L		
Depth with door at 90° 46.13" (117 cm Capacity 3.2 cu.ft. (91 L		
Capacity 3.2 cu.ft. (91 L		
Defrost Type Manua		
Door White		
Cabinet White		
US Electrical Safety ET		
Canadian Electrical ETL-0 Safety		
Amps 1.:		
Voltage/Frequency 115 V AC/60 H		
Weight 105.0 lbs. (48 kg		
Parts & Labor Warranty 1 Year		
Compressor Warranty 5 Year		
UPC 76110105802		
Freezer		
Door Swing RHI		
Reversible Factory Reversible		
Height Adjustable		
Interior Height 24.25" (62 cm		
Interior Width 17.75" (45 cm		
Interior Depth 16.5" (42 cm		
Thermostat Type Dia		
Fan Type Exterio		
Refrigerant Type R134		
Refrigerant Amount 2.7 oz		
High Side PSI 235.		
Low Side PSI 70.		
Level Legs		
Level Legs		

Compressor Step Width	17.75" (45 cm)
Compressor Step Depth	6.0" (15 cm)
Temperature Range	-12°C to -25°C

