

FF511L-FS407LSTACKMED2



67.38" x 19.75" x 22.63" (H x W x D)

FF511LBIMED2 vaccine all-refrigerator stacked with FS407LBIMED2 manual defrost all-freezer, both with locks, digital controls, and NIST calibrated alarm/thermometers

Highlights:

Independent refrigerator and freezer storage in one slim-fitting footprint for space-challenged facilities

Specially designed and featured to meet the CDC, VFC and VFA's guidelines for safe vaccine storage

Assembled in the USA from domestic and imported components

Product Features:

Space-saving design	Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint
Meets CDC & VFC guidelines	Designed to comply with the most current guidelines for vaccine storage
FF511LBIMED2 all-refrigerator	4.1 cu.ft. auto defrost medical all-refrigerator with digital controls, internal fan-forced cooling, adjustable wire shelves, and a flat door liner
FS407LBIMED2 all-freezer	Manual defrost all-freezer with four slide-out storage baskets
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience
Access ports	Rear-mounted 3/8" access port in both units allows users to install their own monitoring equipment
High/low temperature alarms	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated temperature display	Alarms include continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button

FF511L-FS407LSTACKMED2 Specifications:

Overview	
Height of Cabinet	67.38" (171 cm)
Width	19.75" (50 cm)
Depth	22.63" (57 cm)
Depth with Handle	24.63" (63 cm)
Depth with door at 90°	40.75" (104 cm)
Capacity	6.9 cu.ft. (195 L)
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101058740
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Interior Drawers	Yes
Drawer Qty	4
Interior Light	Yes
Refrigerator - Interior Height	28.5" (72 cm)
Refrigerator - Interior Width	15.75" (40 cm)
Refrigerator - Interior Depth	18.0" (46 cm)
Refrigerator - Capacity	4.1 cu.ft
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	3
Refrigerator - Temperature Range	2° to 8°C
Refrigerator - Refrigerant Type	R134a
Refrigerator - Refrigerant Amount	1.75 oz.
Freezer - Interior Height	26.38" (67 cm)
Freezer - Interior Width	14.0" (36 cm)
Freezer - Interior Depth	16.75" (43 cm)
Freezer - Capacity	2.8 cu.ft

Thermostat Type	Digital
Fan Type	Interior and Exterior
Freezer - Temperature Range	-20° to -15°C
Freezer - Refrigerant Type	R134a
Freezer - Refrigerant Amount	3.0 oz.

