FFAR10-FS30LSTACKMED2



83.63" x 24" x 23.5" (H x W x D)

Stacked combination of FFAR10MED2 auto defrost allrefrigerator and FS30LMED2 compact manual defrost allfreezer, both with locks, digital controls, and NIST calibrated alarm/thermometers

Highlights:

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

Independent refrigerator and freezer storage in one slimfitting footprint for space-challenged facilities

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Product Features:

Space-saving design	Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint	
Meets CDC & VFC guidelines	Designed to comply with the most current guidelines for vaccine storage	
FFAR10MED2 all-refrigerator	10.1 cu.ft. auto defrost all-refrigerator with digital controls, internal fan, flat door liner, and adjustable shelving	
FS30LMED2 all-freezer	Compact manual defrost all-freezer with digital thermostat and wire shelving	
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top	
Digital thermostats	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience	
Access ports	Rear-mounted 3/8" access port in both units allows users to install their own monitoring equipment	
High/low temperature alarms	Audible alarm sounds if the interior temperature rises or falls out of set range	
NIST calibrated temperature display	Alarms include continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	

accuc@ld

FFAR10-FS30LSTACKMED2 Specifications:

Overview			
Height of Cabinet	83.63" (212 cm)		
Width	24.0" (61 cm)		
Depth	23.5" (60 cm)		
Depth with Handle	24.75" (63 cm)		
Depth with door at 90°	45.5" (116 cm)		
Capacity	12.1 cu.ft. (343 L)		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Voltage/Frequency	115 V AC/60 Hz		
Shipping Weight	198.0 lbs. (90 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101058856		
Refrigerator-Freezer			
Door Swing	RHD		
Reversible	Factory Reversible		
Adjustable Shelves	Yes		
Interior Light	Yes		
Refrigerator - Interior Height	48.25" (123 cm)		
Refrigerator - Interior Width	20.5" (52 cm)		
Refrigerator - Interior Depth	17.75" (45 cm)		
Refrigerator - Capacity	10.1 cu.ft		
Refrigerator - Shelf Type	Wire		
Refrigerator - Shelf Qty	4		
Refrigerator - Temperature Range	2°C to 8°C		
Refrigerator - Refrigerant Type	R134a		
Refrigerator - Refrigerant Amount	3.0 oz.		
Freezer - Interior Height	18.5" (47 cm)		
Freezer - Interior Width	13.5" (34 cm)		
Freezer - Interior Depth	13.0" (33 cm)		
Freezer - Capacity	1.8 cu.ft		
Freezer - Shelf Type	Wire		

Freezer - Shelf Qty	2
Thermostat Type	Digital
Fan Type	Interior
Freezer - Temperature Range	-20° to -15°C
Freezer - Refrigerant Type	R600a
Freezer - Refrigerant Amount	0.8 oz.

