

FFAR24L-FS24LSTACKMED2



40.38" x 19" x 19" (H x W x D)

Stacked combination of FFAR24LMED2 auto defrost all-refrigerator and FS24LMED2 compact manual defrost all-freezer, both with locks, digital controls, and NIST calibrated alarm/thermometers

Highlights:

Specially designed and featured to meet the CDC, VFC and VFA's guidelines for safe vaccine storage

Assembled in the USA from domestic and imported components

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Product Features:

Meets CDC & VFC guidelines	Designed to comply with the most current guidelines for vaccine storage
Space-saving design	Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint
FFAR24LMED2 all-refrigerator	Compact auto defrost all-refrigerator fully featured with digital controls and an internal fan
FS24LMED2 all-freezer	Compact manual defrost all-freezer with digital thermostat and wire shelving
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top
Access ports	Rear-mounted 3/8" access port in both units allows users to install their own monitoring equipment
High/low temperature alarms	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated temperature display	Alarms include continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Buffered temperature probes	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines

FFAR24L-FS24LSTACKMED2 Specifications:

Overview	
Height of Cabinet	40.38" (103 cm)
Width	19.0" (48 cm)
Depth	19.0" (48 cm)
Capacity	3.1 cu.ft. (88 L)
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101058894
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Refrigerator - Interior Height	16.63" (42 cm)
Refrigerator - Interior Width	15.0" (38 cm)
Refrigerator - Interior Depth	13.25" (34 cm)
Refrigerator - Capacity	1.7 cu.ft
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	2
Refrigerator - Temperature Range	2° to 8°C
Refrigerator - Refrigerant Type	R134a
Refrigerator - Refrigerant Amount	1.13 oz.
Freezer - Interior Height	14.38" (37 cm)
Freezer - Interior Width	13.5" (34 cm)
Freezer - Interior Depth	13.25" (34 cm)
Freezer - Capacity	1.4 cu.ft
Freezer - Shelf Type	Wire
Freezer - Shelf Qty	1
Thermostat Type	Digital
Fan Type	Interior
Freezer - Temperature Range	-20° to -15°C

Freezer - Refrigerant Type

Freezer - Refrigerant Amount

