

FS407LPRO



34" x 19.25" x 21.38" (H x W x D)

20" wide all-freezer for freestanding use, manual defrost with a lock and probe hole

Highlights:

Slim 20" width is ideal for any setting

Factory installed access port allows users to install their own monitoring equipment

Factory installed lock provides security you can count on

Product Features:

Slim 20" width	Full 2.8 cu.ft. capacity inside conveniently slim footprint
Access port	Includes a factory installed probe hole for users to install their own monitoring equipment
Factory installed lock	Top-mounted for convenient security
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Pull-out drawers	Four clear baskets for convenient and separated storage
-20° capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Adjustable thermostat	Rear mounted to prevent accidental adjustments
Magnetic door gasket	Quality door gaskets ensure a tight seal for energy savings and improved performance

FS407LPRO Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Height to Hinge Cap	34.0" (86 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with Handle	23.0" (58 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	2.8 cu.ft. (79 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.6
Voltage/Frequency	115 V AC/60 Hz
Weight	70.0 lbs. (32 kg)
Shipping Weight	73.0 lbs. (33 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101057132
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	26.38" (67 cm)
Interior Width	14.0" (36 cm)
Interior Depth	16.75" (43 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	3.0 oz.
High Side PSI	210.0
Low Side PSI	105.0
Level Legs	2
Interior Drawers	Yes
Drawers Qty	4

