

# PHC61G-SCR610BLSTACK



74" x 24" x 23.5" (H x W x D)

Glass door warming cabinet PHC61G stacked with SCR610BL commercial beverage center

## Highlights:

Combines our popular commercial beverage center with our leading blanket warmer

Glass door warming cabinet keeps full blanket inventory in easy view

Digital controls for both units ensure easy temperature management

## Product Features:

Space-saving design	Allows you to create a full refrigerator-blanket warmer combination with independent controls in a slim-fitting footprint
Slim 24" footprint	Ideally sized for use in space-challenged facilities
SCR610BL display refrigerator	5 cu.ft. commercial all-refrigerator with digital controls and automatic defrost operation for low maintenance storage with full visibility
PHC61G warming cabinet	PureTherm glass door warming cabinet with 5 cu.ft. interior to hold blankets at their ideal temperature
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator and place and secure the warming cabinet on top
ENERGY STAR qualified (refrigerator only)	SCR610BL meets ENERGY STAR standards as a commercial refrigerator
Stainless steel interior (both units)	Offers lasting durability and improved sanitary conditions
Stainless steel trimmed double pane tempered glass door (both units)	Heat-safe doors offer a full view of both interiors
Adjustable cantilevered shelves (both units)	Cantilevered chrome shelving offers a variety of configurations to accommodate different sized items

## PHC61G-SCR610BLSTACK Specifications:

Overview			
Height of Cabinet	74.0" (188 cm)	Adjustable Shelves (Bottom Unit)	Yes
Width	24.0" (61 cm)	Shelf Type (Bottom Unit)	Chrome
Depth	23.5" (60 cm)	Shelf Quantity (Bottom Unit)	3
Depth with Handle	25.38" (64 cm)	Interior Light (Bottom Unit)	Yes
Depth with door at 90°	45.5" (116 cm)	Thermostat Type (Bottom Unit)	Digital
Capacity	10.0 cu.ft. (283 L)	Temperature Range (Bottom Unit)	36°F to 43°F
Defrost Type	Automatic	Interior Height (Bottom Unit)	25.0" (64 cm)
Door	Glass	Interior Width (Bottom Unit)	19.38" (49 cm)
Cabinet	Black	Interior Depth (Bottom Unit)	17.38" (44 cm)
US Electrical Safety	ETL	Capacity (Bottom Unit)	5.0cu.ft.
Canadian Electrical Safety	ETL-C	Refrigerant Type	R600a
Sanitation	ETL-S	Refrigerant Amount	0.99 oz.
Amps	1.5	High Side PSI	270.0
Voltage/Frequency	115 V AC/60 Hz	Low Side PSI	105.0
Shipping Weight	149.5 lbs. (68 kg)	Fan Type	Interior and Exterior
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101059280		
Warming & Cooling Cabinet			
Top Unit	Warming Cabinet		
Door Swing (Top Unit)	RHD		
Reversible (Top Unit)	Yes		
Adjustable Shelves (Top Unit)	Yes		
Shelf Type (Top Unit)	Chrome		
Shelf Quantity (Top Unit)	2		
Thermostat Type (Top Unit)	Digital		
Temperature Range (Top Unit)	120 to 150°F		
Interior height (Top Unit)	26.0" (66 cm)		
Interior Width (Top Unit)	20.0" (51 cm)		
Interior Depth (Top Unit)	19.5" (50 cm)		
Capacity (Top Unit)	5.0 cu.ft. (142 L)		
Refrigeration Unit	All-Refrigerator		
Door Swing (Bottom Unit)	RHD		
Reversible (Bottom Unit)	Yes		

