



# SBC695OSTWIN



34.25" x 23.75" x 25" (H x W x D)

Outdoor/indoor commercial beer dispenser for built-in or freestanding use, with complete dual tap kit, digital thermostat, and 304 grade stainless steel exterior

**Highlights:**

- Commercially listed to NSF-7 standards
- Flexible design allows built-in or freestanding use in 24" spaces
- Weatherproof design ensures safe operation in the outdoors

**Product Features:**

|                           |   |
|---------------------------|---|
| Commercially approved     | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings                                       |
| Weatherproof design       | Solid construction allows placement in the outdoors   |
| Built-in capable          | Front-breathing design allows fully recessed installation under counters  |
| Full-sized beer dispenser | Large interior can accept a full half barrel keg, two slim quarter kegs, or up to three sixth barrel or Cornelius style kegs      |
| Complete tap kit          | Includes a 5 lb. CO2 tank and regulator, dual tap draft arm, Sankey American tap, connection hardware, and cleaning kit           |
| Dual tap system           | Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs   |
| Stainless steel exterior  | Door and cabinet are wrapped in 304 grade stainless steel for lasting durability in the outdoors                                  |
| Professional handle       | Blade style handle in brushed stainless steel matches many popular styles of cabinetry and grill details                          |
| Digital thermostat        | Electronic controls ensure easy temperature management for optimum beer storage, with a readout viewable in Celsius or Fahrenheit |

# SBC695OSTWIN Specifications:

| Overview                   |                       |
|----------------------------|-----------------------|
| Height of Cabinet          | 34.25" (87 cm)        |
| Width                      | 23.75" (60 cm)        |
| Depth                      | 25.0" (64 cm)         |
| Depth with Handle          | 26.88" (68 cm)        |
| Depth with door at 90°     | 47.75" (121 cm)       |
| Capacity                   | 6.04 cu.ft. (171 L)   |
| Defrost Type               | Automatic             |
| Door                       | Stainless Steel       |
| Cabinet                    | Stainless Steel       |
| US Electrical Safety       | ETL                   |
| Canadian Electrical Safety | ETL-C                 |
| Sanitation                 | ETL-S                 |
| Amps                       | 1.3                   |
| Voltage/Frequency          | 115 V AC/60 Hz        |
| Weight                     | 108.0 lbs. (49 kg)    |
| Parts & Labor Warranty     | 1 Year                |
| Compressor Warranty        | 5 Years               |
| UPC                        | 761101060903          |
| Kegeerator                 |                       |
| Door Swing                 | RHD                   |
| Reversible                 | Yes                   |
| Tap Kit                    | Yes                   |
| Height with Tap            | 50.38" (128 cm)       |
| Number of Taps             | 2                     |
| Thermostat Type            | Digital               |
| Interior Light             | Yes                   |
| Fan Type                   | Interior and Exterior |
| Refrigerant                | R600a                 |
| Refrigerant Amount         | 1.76 oz.              |
| High Side PSI              | 220.0                 |
| Low Side PSI               | 43.0                  |
| Inter Height               | 27.0" (69 cm)         |
| Interior Width             | 20.38" (52 cm)        |
| Interior Depth             | 21.25" (54 cm)        |
| Compressor Step Height     | 5.5" (14 cm)          |
| Compressor Step Width      | 9.63" (24 cm)         |
| Compressor Step Depth      | 2.5" (6 cm)           |

|                   |                 |
|-------------------|-----------------|
| Wheel Qty         | 4               |
| Surface           | Stainless Steel |
| Temperature Range | 32° to 50°F     |

