# SBC695OSNCF



#### 34.25" x 23.75" x 25" (H x W x D)

Outdoor/indoor commercial nitro-infused coffee dispenser for built-in or freestanding use, with complete tap kit, digital thermostat, and 304 grade stainless steel exterior

### **Highlights:**

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Commercial grade tap kit includes everything you need to serve creamy nitro-infused coffee on draft

### **Product Features:**

Dispenses nitro-infused coffee	Stout style tap allows you to serve smooth nitro-infused cold brew on tap
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings
Weatherproof design	Solid construction allows placement in the outdoors
Built-in capable	Front-breathing design allows fully recessed installation under counters
Full-sized coffee dispenser	Large interior can accept up to three cornelius kegs
Complete tap kit	Commercial grade tap kit includes a stainless steel stout tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs
Stainless steel exterior	Door and cabinet are wrapped in 304 grade stainless steel for lasting durability in the outdoors
Professional handle	Blade style handle in brushed stainless steel matches many popular styles of cabinetry and grill details
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com





## SBC695OSNCF Specifications:

34.25" (87 cm) 23.75" (60 cm) 25.0" (64 cm) 26.88" (68 cm) 47.75" (121 cm) 5.04 cu.ft. (171 L) Automatic Stainless Steel Stainless Steel ETL- ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989 RHD
25.0" (64 cm) 26.88" (68 cm) 47.75" (121 cm) 5.04 cu.ft. (171 L) Automatic Stainless Steel Stainless Steel ETL-C ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
26.88" (68 cm) 47.75" (121 cm) 5.04 cu.ft. (171 L) Automatic Stainless Steel Stainless Steel ETL ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
47.75" (121 cm) 3.04 cu.ft. (171 L) Automatic Stainless Steel Stainless Steel ETL-C ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
5.04 cu.ft. (171 L) Automatic Stainless Steel Stainless Steel ETL-C ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
Automatic Stainless Steel Stainless Steel ETL ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
Stainless Steel Stainless Steel ETL-C ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
Stainless Steel ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
ETL ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
ETL-C ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
ETL-S 1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
1.3 115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
115 V AC/60 Hz 108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
108.0 lbs. (49 kg) 1 Year 5 Years 761101060989
1 Year 5 Years 761101060989
5 Years 761101060989
761101060989
RHD
RHD
Yes
Yes
50.38" (128 cm)
1
Digital
Yes
Interior and Exterior
R600a
1.76 oz.
220.0
43.0
27.0" (69 cm)
20.38" (52 cm)
21.25" (54 cm)
21.25" (54 cm) 5.5" (14 cm)

4
Stainless Steel
32º to 50ºF



