accuc@ld

FF511LBI7NZADA



32.25" x 19.25" x 21.38" (H x W x D)

Commercially approved ADA compliant Nutrition Center series all-refrigerator in white for built-in or freestanding use, with front lock and digital temperature display

Highlights:

Commercially approved to NSF-7 standards

Digital temperature display and audible alarm allows easier temperature monitoring as recommended by JCAHO

Thermometer is NIST calibrated in our ISO/IEC 17025:2017 laboratory

Product Features:

| Commercially approved | ETL-S listed to NSF-7 commercial standards for food and beverage storage | |
|-------------------------------------|---|--|
| ADA compliant | Sized at 32" high for use under lower ADA compliant counters | |
| 20" width | Uniquely slim width is ideal for facilities with limited floor space | |
| Built-in capable | Make the best use of space by installing your appliance under the counter and flush with other cabinets | |
| NIST calibrated temperature display | Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button | |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range | |
| Versatile display | Temperature display can be switched from Celsius to Fahrenheit at the touch of a button | |
| Factory installed lock | Keyed lock conveniently located towards the top of the door for added security (2 keys included) | |
| Automatic defrost | Reduced maintenance with auto defrost system | |



accuc@ld

FF511LBI7NZADA Specifications:

| Overview | | |
|-------------------------------|--------------------|--|
| Height of Cabinet | 32.0" (81 cm) | |
| Height to Hinge Cap | 32.25" (82 cm) | |
| Width | 19.25" (49 cm) | |
| Depth | 21.38" (54 cm) | |
| Depth with Handle | 23.0" (58 cm) | |
| Depth with door at 90° | 39.5" (100 cm) | |
| Capacity | 4.1 cu.ft. (116 L) | |
| Defrost Type | Automatic | |
| Door | White | |
| Cabinet | White | |
| US Electrical Safety | ETL | |
| Canadian Electrical Safety | ETL-C | |
| Sanitation | ETL-S | |
| Amps | 1.4 | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Weight | 65.0 lbs. (29 kg) | |
| Shipping Weight | 80.0 lbs. (36 kg) | |
| Parts & Labor Warranty | 1 Year | |
| Compressor Warranty | 5 Years | |
| UPC | 761101061108 | |
| Refrigerator Features | | |
| Door Swing | RHD | |
| Reversible | Factory Reversible | |
| Crisper Qty | 1 | |
| Crisper Finish | Transparent | |
| Crisper Cover | Glass | |
| Shelf Type | Wire | |
| Shelf Qty | 3 | |
| Adjustable Shelves | Yes | |
| Thermostat Type | Dial | |
| Refrigerant Type | R134a | |
| Refrigerant Amount | 1.75oz. | |
| High Side PSI | 205.0 | |
| Low Side PSI | 103.0 | |
| Interior Light | Yes | |
| Temperature Range | 35 to 39°F | |
| Dimensions | | |

| Interior Height | 28.5" (72 cm) |
|------------------------|----------------|
| Interior Width | 15.75" (40 cm) |
| Interior Depth | 18.0" (46 cm) |
| Compressor Step Height | 8.0" (20 cm) |
| Compressor Step Width | 17.0" (43 cm) |
| Compressor Step Depth | 6.75" (17 cm) |





