

# SCR312LNZ



26.13" x 17" x 19.25" (H x W x D)

Commercially approved compact Nutrition Center series glass door all-refrigerator with front lock and digital temperature display

## Highlights:

Commercially approved to NSF-7 standards

Digital temperature display and audible alarm allows easier temperature monitoring as recommended by JCAHO

Thermometer is NIST calibrated in our ISO/IEC 17025:2017 laboratory

## Product Features:

|                                     |   |
|-------------------------------------|---|
| Commercially approved               | ETL-S listed to NSF-7 commercial standards for food and beverage storage  |
| High/low temperature alarm          | Audible alarm sounds if the interior temperature rises or falls out of set range  |
| NIST calibrated temperature display | Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button |
| Versatile display                   | Temperature display can be switched from Celsius to Fahrenheit at the touch of a button   |
| Double pane tempered glass door     | Heat resistant design provides clear view of stored products, with an elegant trim in stainless steel   |
| Professional handle                 | 17 1/2" long handle in brushed aluminum   |
| Factory installed lock              | Keep contents secure with a front lock on the door  |
| Automatic defrost                   | No-frost convenience for reduced user maintenance   |
| Digital thermostat                  | Precise temperature management at the touch of a button, with an external display for added convenience   |

## SCR312LNZ Specifications:

| Overview                   |                   |
|----------------------------|-------------------|
| Height of Cabinet          | 28.0" (71 cm)     |
| Height to Hinge Cap        | 26.13" (66 cm)    |
| Width                      | 17.0" (43 cm)     |
| Depth                      | 19.25" (49 cm)    |
| Depth with Handle          | 21.0" (53 cm)     |
| Depth with door at 90°     | 35.25" (90 cm)    |
| Capacity                   | 2.5 cu.ft. (71 L) |
| Defrost Type               | Automatic         |
| Door                       | Glass             |
| Cabinet                    | Black             |
| US Electrical Safety       | ETL               |
| Canadian Electrical Safety | ETL-C             |
| Sanitation                 | ETL-S             |
| Amps                       | 1.3               |
| Voltage/Frequency          | 115 V AC/60 Hz    |
| Weight                     | 80.0 lbs. (36 kg) |
| Parts & Labor Warranty     | 1 Year            |
| Compressor Warranty        | 5 Years           |
| UPC                        | 761101061177      |
| Refrigerator Features      |                   |
| Door Swing                 | RHD               |
| Reversible                 | No                |
| Shelf Type                 | Wire              |
| Shelf Qty                  | 4                 |
| Adjustable Shelves         | Yes               |
| Thermostat Type            | Digital           |
| Refrigerant Type           | R600a             |
| Refrigerant Amount         | 0.92oz.           |
| High Side PSI              | 270.0             |
| Low Side PSI               | 103.0             |
| Level Legs Qty             | 2                 |
| Interior Light             | Yes               |
| Temperature Range          | 34°F to 43°F      |
| Sound Level                | 33.5 dB           |
| Dimensions                 |                   |
| Interior Height            | 20.5" (52 cm)     |
| Interior Width             | 13.5" (34 cm)     |
| Interior Depth             | 14.75" (37 cm)    |

|                        |               |
|------------------------|---------------|
| Compressor Step Height | 7.5" (19 cm)  |
| Compressor Step Width  | 13.5" (34 cm) |
| Compressor Step Depth  | 5.25" (13 cm) |

