

SCR486LNZ



33.5" x 19" x 19.5" (H x W x D)

Commercially approved Nutrition Center series glass door all-refrigerator for freestanding use, with front lock and digital temperature display

Highlights:

Commercially approved to NSF-7 standards

Digital temperature display and audible alarm allows easier temperature monitoring as recommended by JCAHO

Thermometer is NIST calibrated in our ISO/IEC 17025:2017 laboratory

Product Features:

| | |
|-------------------------------------|---|
| Commercially approved | ETL-S listed to NSF-7 standards for use in commercial settings |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range |
| NIST calibrated temperature display | Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button |
| Versatile display | Temperature display can be switched from Celsius to Fahrenheit at the touch of a button |
| Double pane tempered glass door | Heat resistant design provides clear view of stored products, with an elegant trim in stainless steel |
| Digital thermostat | Precise temperature management at the touch of a button, with an external display for added convenience |
| Recessed LED lighting | Externally located controls make it easy to manage the interior light, keeping products in full view to increase impulse sales |
| Professional handle | Stainless steel handle adds an attractive touch |
| Factory installed lock | Keyed lock ensures a secure interior |

SCR486LNZ Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 35.5" (90 cm) |
| Height to Hinge Cap | 33.5" (85 cm) |
| Width | 19.0" (48 cm) |
| Depth | 19.5" (50 cm) |
| Depth with Handle | 20.0" (51 cm) |
| Depth with door at 90° | 36.25" (92 cm) |
| Capacity | 3.35 cu.ft. (95 L) |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 77.0 lbs. (35 kg) |
| Shipping Weight | 116.0 lbs. (53 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101061184 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | No |
| Shelf Type | Chrome |
| Shelf Qty | 4 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Refrigerant Type | R600a |
| Refrigerant Amount | 0.92oz. |
| High Side PSI | 270.0 |
| Low Side PSI | 103.0 |
| Level Legs Qty | 2 |
| Interior Light | Yes |
| Dimensions | |
| Interior Height | 28.75" (73 cm) |
| Interior Width | 15.25" (39 cm) |
| Interior Depth | 13.75" (35 cm) |

| | |
|------------------------|----------------|
| Compressor Step Height | 7.75" (20 cm) |
| Compressor Step Width | 15.25" (39 cm) |
| Compressor Step Depth | 5.0" (13 cm) |

