accucold

SCR600LBINZADA



32.38" x 23.63" x 23.5" (H x W x D)

Commercially approved ADA compliant Nutrition Center series glass door all-refrigerator for built-in or freestanding use, with front lock and digital temperature display

Highlights:

Commercially approved to NSF-7 standards

Digital temperature display and audible alarm allows easier temperature monitoring as recommended by JCAHO

Thermometer is NIST calibrated in our ISO/IEC 17025:2017 laboratory

Product Features:

Commercially approved	ETL-S listed to NSF-7 commercial standards for food and beverage storage
ADA Compliant	32 inch height is designed to fit under ADA compliant counters
Factory installed lock	Keyed lock for a secure interior
NIST calibrated temperature display	Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
Versatile display	Temperature display can be switched from Celsius to Fahrenheit at the touch of a button
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry
Double pane tempered glass door	Heat resistant design provides clear view of stored products
Reversible door	Keep placement options flexible with a reversible door swing that is easy to switch when your arrangement changes

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 \checkmark




accuceld

SCR600LBINZADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.38" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.5" (65 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101061214
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Dial
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	1.8oz.
High Side PSI	285.0
Low Side PSI	70.0
Level Legs Qty	2
Interior Light	Yes
Dimensions	
Interior Height	26.0" (66 cm)
Interior Width	20.75" (53 cm)
Interior Depth	17.5" (44 cm)
Compressor Step Height	6.0" (15 cm)
	20.75" (53 cm)
Compressor Step Width	

	4
5.0" (13 cm)	
	- 23 <u>1</u>
	-18
	L
	hl
	JF
	H
	5.0" (13 cm)



TOP VIEW

500



