

## SCFM252W



36.75" x 91.25" x 28.25" (H x W x D)

Commercially listed 26.66 cu.ft. manual defrost chest freezer in white with stainless steel corner guards

## **Highlights:**

Commercially approved for use in foodservice establishments

Palletized and crated to ensure added durability during the shipping process

26.66 cu.ft. interior for large capacity storage

## **Product Features:**

Large capacity	26.66 cu.ft. of interior storage	
Commercially approved	UL-S listed to ANSI-NSF Standard 7 for commercial use	
Packaging safety	Ships on a pallet and boxed in a wooden crate for added protection during shipping	
Factory installed locks	Keyed lock on each handle offers added security (two sets of keys included)	
Manual defrost operation	Static cooling system	
Counterbalanced hinges	Two lids feature weighted lids that will stay open for easier loading and unloading	
Thick insulation	3" thick walls ensure proper insulation for reliable storage	
Stainless steel front corner protectors	External "bumpers" are factory installed to protect the unit's front corners from dents	
Hammered aluminum interior	Solid construction for durable storage in busy settings	





## **SCFM252W Specifications:**

Overview		
Height of Cabinet	36.75" (93 cm)	
Width	91.25" (232 cm)	
Depth	28.25" (72 cm)	
Depth with Handle	30.0" (76 cm)	
Capacity	26.66 cu.ft. (755 L)	
Defrost Type	Manual	
Door	White	
Cabinet	White	
US Electrical Safety	UL	
Canadian Electrical Safety	ULC	
Sanitation	UL-S	
Amps	3.8	
Voltage/Frequency	115 V AC/60 Hz	
Weight	250.0 lbs. (113 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101061023	
Freezer		
Door Swing	Lift-Up	
Interior Height	27.5" (70 cm)	
Interior Width	85.5" (217 cm)	
Interior Depth	20.75" (53 cm)	
Thermostat Type	Dial	
Refrigerant Type	R134a	
Refrigerant Amount	10.6 oz.	
High Side PSI	220.0	
Low Side PSI	90.0	
Wheels	6	
Compressor Step Height	9.75" (25 cm)	
Compressor Step Width	9.0" (23 cm)	
Compressor Step Depth	9.0" (23 cm)	
Temperature Range	-10 to -26°C	

