

SBC58BBIIFCMTWINADA



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap combo nitro/cold brew coffee dispenser with panelready door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro-infused cold brew drafts

Commercially listed to NSF-7 standards

Product Features:

Dispenses both flat and nitro-infused coffee	Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro-infused drafts from two cornelius kegs
ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings
Built-in capable	Front-breathing design allows fully recessed installation under counters
Complete tap kit	Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs
Dual tap system	Twin style draft tower allows you to serve from two cornelius style kegs
Panel-ready door	Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)
Adjustable thermostat	Interior dial thermostat ensures easy temperature management
Automatic defrost	No-frost operation for minimum user maintenance





SBC58BBIIFCMTWINADA Specifications:

Height of Cabinet	32.0" (81 cm)	
Height to Hinge Cap	32.25" (82 cm)	
Width	23.63" (60 cm)	
Depth	22.75" (58 cm)	
Depth with door at 90°	45.0" (114 cm)	
Capacity	5.5 cu.ft. (156 L)	
Defrost Type	Automatic	
Door	Panel-Ready	
Cabinet	Black	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	1.3	
Voltage/Frequency	115 V AC/60 Hz	
Weight	110.0 lbs. (50 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101064734	
Kegerator		
Door Swing	RHD	
Reversible	Factory Reversible	
Tap Kit	Vaa	
	Yes	
Number of Taps	2	
Number of Taps Thermostat Type		
<u> </u>	2	
Thermostat Type	2 Dial	
Thermostat Type Interior Light	2 Dial Yes	
Thermostat Type Interior Light Fan Type	Dial Yes Exterior	
Thermostat Type Interior Light Fan Type Refrigerant	Dial Yes Exterior R134a	
Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount	Dial Yes Exterior R134a 1.8 oz.	
Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI	Dial Yes Exterior R134a 1.8 oz. 285.0	
Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI	2 Dial Yes Exterior R134a 1.8 oz. 285.0 88.0	
Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height	2 Dial Yes Exterior R134a 1.8 oz. 285.0 88.0 25.75" (65 cm)	
Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height Interior Width	2 Dial Yes Exterior R134a 1.8 oz. 285.0 88.0 25.75" (65 cm) 21.0" (53 cm)	
Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height Interior Width Interior Depth	2 Dial Yes Exterior R134a 1.8 oz. 285.0 88.0 25.75" (65 cm) 21.0" (53 cm) 17.75" (45 cm)	
Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height Interior Width Interior Depth Compressor Step Height	2 Dial Yes Exterior R134a 1.8 oz. 285.0 88.0 25.75" (65 cm) 21.0" (53 cm) 17.75" (45 cm) 6.5" (17 cm)	





