

SCR23SSG



83.75" x 27.5" x 31" (H x W x D)

23 cu.ft. commercial reach-in refrigerator in complete stainless steel with glass door

Highlights:

Commercially listed to NSF standards

Stainless steel interior and exterior cabinet for true durability in high traffic commercial settings

Glass door provides a full display of stored products

Product Features:

Complete stainless steel construction	Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup	
Glass door	Full display of the interior, with an anti-condensate door frame heater to ensure a clear view	
Forced air cooling	Top-mounted commercial fan ensures rapid temperature recovery	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	
Self-closing door	Closes to save energy but will remain open when the door is opened at a 90° angle for easier loading	
Open door alarm	Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will sound continuously if the door is open for more than 5 minutes	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Commercial grade casters	Ships with a set of casters (2 locking) for easy mobility as needed	
Microprocessor control panel	Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799





SCR23SSG Specifications:

Overview	
Nominal Height	84.0" (213 cm)
Height of Cabinet	83.75" (213 cm)
Nominal Width	28.0" (71 cm)
Width	27.5" (70 cm)
Nominal Depth	31.0" (79 cm)
Depth	31.0" (79 cm)
Depth with Handle	32.75" (83 cm)
Depth with door at 90°	56.5" (144 cm)
Capacity	23.0 cu.ft. (651 L)
Defrost Type	Automatic
Door	Glass
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	7.5
Voltage/Frequency	115 V AC/60 Hz
Weight	282.0 lbs. (128 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101062396
Refrigerator Features	
Door Swing	RHD
Door Swing Reversible	RHD
3	
Reversible	No
Reversible Shelf Type	No Wire
Reversible Shelf Type Shelf Qty	No Wire 4
Reversible Shelf Type Shelf Qty Adjustable Shelves	No Wire 4 Yes
Reversible Shelf Type Shelf Qty Adjustable Shelves Thermostat Type	No Wire 4 Yes Digital
Reversible Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type	No Wire 4 Yes Digital Interior
Reversible Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type	No Wire 4 Yes Digital Interior R290
Reversible Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	No Wire 4 Yes Digital Interior R290 2.5oz.
Reversible Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI	No Wire 4 Yes Digital Interior R290 2.5oz. 290.0
Reversible Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	No Wire 4 Yes Digital Interior R290 2.5oz. 290.0 155.0
Reversible Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Wheel Qty	No Wire 4 Yes Digital Interior R290 2.5oz. 290.0 155.0 4

Dimensions		
Interior Height	51.5" (131 cm)	
Interior Width	23.5" (60 cm)	
Interior Depth	27.0" (69 cm)	

