

SCR49SSG



83.75" x 55.25" x 31" (H x W x D)

49 cu.ft. commercial reach-in refrigerator in complete stainless steel with glass doors

Highlights:

Commercially listed to NSF standards

Glass doors provide a full display of stored products

Stainless steel interior and exterior cabinet for true durability in high traffic commercial settings

Product Features:

Complete stainless steel construction	Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup	
Forced air cooling	Top-mounted commercial fan ensures rapid temperature recovery	
Glass door	Full display of the interior, with an anti-condensate door frame heater to ensure a clear view	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	
Self-closing doors	Closes to save energy but will remain open when the door is opened at a 90° angle for easier loading	
Open door alarm	Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will sound continuously if the door is open for more than 5 minutes	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Commercial grade casters	Ships with a set of casters (2 locking) for easy mobility as needed	
Microprocessor control panel	Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799





SCR49SSG Specifications:

Overview	
Nominal Height	84.0" (213 cm)
Height of Cabinet	83.75" (213 cm)
Nominal Width	56.0" (142 cm)
Width	55.25" (140 cm)
Nominal Depth	31.0" (79 cm)
Depth	31.0" (79 cm)
Depth with Handle	32.75" (83 cm)
Depth with door at 90°	56.5" (144 cm)
Capacity	49.0 cu.ft. (1388 L)
Defrost Type	Automatic
Door	Glass
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	7.5
Voltage/Frequency	115 V AC/60 Hz
Weight	441.0 lbs. (200 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101062402
Refrigerator Features	
Door Swing	French
Shelf Type	Wire
Shelf Qty	8
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R290
Refrigerant Amount	3.2oz.
High Side PSI	290.0
Low Side PSI	155.0
Wheel Qty	4
Interior Light	Yes
Temperature Range	33 to 41ºF
Dimensions	
Interior Height	51.5" (131 cm)

Interior Width	51.5" (131 cm)
Interior Depth	27.0" (69 cm)





