SCFF497



Product Features:

Commercially approved Commercial construction meeting UL commercial listing standards Complete stainless steel construction Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup Forced air cooling Top-mounted commercial fan ensures rapid temperature recovery Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup defrost Closes to save energy but will remain open when the door is opened at a 90° angle for easier Self-closing doors loading Open door alarm Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will sound continuously if the door is open for more than 5 minutes Temperature alarm Visual and audible alarms alert if the interior temperature rises or falls out of set range Commercial grade casters Ships with a set of casters (2 locking) for easy mobility as needed Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature Microprocessor control panel

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified

management

stainless steel

Highlights:

Commercially listed to NSF standards

83.75" x 55.25" x 31" (H x W x D)

Stainless steel interior and exterior cabinet for true durability in high traffic commercial settings

49 cu.ft. commercial reach-in all-freezer in complete


Optimized forced air cooling for excellent temperature stability and uniformity with rapid recovery after door openings and product loading

www.summitappliance.com

FAX 844-478-8799 info@sumr

info@summitappliance.com







SCFF497 Specifications:

Overview	
Nominal Height	84.0" (213 cm)
Height of Cabinet	83.75" (213 cm)
Nominal Width	56.0" (142 cm)
Width	55.25" (140 cm)
Nominal Depth	31.0" (79 cm)
Depth	31.0" (79 cm)
Depth with door at 90°	56.5" (144 cm)
Capacity	49.0 cu.ft. (1388 L)
Defrost Type	Frost-Free
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	10.5
Voltage/Frequency	115 V AC/60 Hz
Weight	428.0 lbs. (194 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101062389
Freezer	
Door Swing	French
Interior Height	51.5" (131 cm)
Interior Width	51.5" (131 cm)
Interior Depth	27.0" (69 cm)
Shelf Type	Wire
Shelf Qty	8
Adjustable Shelves	Yes
Thermostat Type	Digital
Interior Light	Yes
Fan Type	Interior
Refrigerant Type	R290
Refrigerant Amount	4.6 oz.
Wheels	4
willeel3	



