

NOVA35PDC



45.5" x 43" x 27.25" (H x W x D)

43" wide fully assembled commercial dipping cabinet made in Europe with digital thermostat, sneezeguard, and light

Highlights:

Fully assembled dipping cabinet with durable polycarbonate sneezeguard and light

Digital thermostat for easy temperature control, with a wide range between -13 and 23°F to accommodate ice cream, gelato, and other frozen treats

Tub holder baskets for convenient ice cream storage

Product Features:

Commercially approved	UL-S listed to NSF-7 Standards for use in commercial establishments	
Sneezeguard	Durable polycarbonate sneezeguard with light is pre-installed	
Digital thermostat	Electronic controls for more precise temperature management	
Wide temperature range	Digital thermostat can be set between -13 and +23°F to accommodate a variety of frozen treats	
Ice cream tub holders	Three epoxy coated wire baskets with plastic lids included to hold standard ice cream tubs in place	
Holds 10 standard 3 gallon tubs	Unit can store 4 tubs on the floor and display an additional 6 using the provided baskets	
Sliding glass lid	Two tempered glass lids on ball-bearing glides slide open and closed easily for added efficiency	
Strong insulation	3" thick insulation helps to ensure items stay cold	
Manual defrost	Static cooling system for improved temperature stability	







NOVA35PDC Specifications:

Overview		
Nominal Height	46.0" (117 cm)	
Height of Cabinet	45.5" (116 cm)	
Nominal Width	43.0" (109 cm)	
Width	43.0" (109 cm)	
Nominal Depth	28.0" (71 cm)	
Depth	27.25" (69 cm)	
Capacity	11.7 cu.ft. (331 L)	
Defrost Type	Manual	
Door	Glass	
Cabinet	White	
US Electrical Safety	UL	
Canadian Electrical Safety	ULC	
Sanitation	UL-S	
Amps	7.2	
Voltage/Frequency	115 V AC/60 Hz	
Weight	152.0 lbs. (69 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101064895	
Freezer		
Door Swing	Sliding	
Interior Height	26.0" (66 cm)	
Interior Width	36.75" (93 cm)	
Interior Depth	21.0" (53 cm)	
Thermostat Type	Digital	
Refrigerant Type	R290	
Refrigerant Amount	3.03 oz.	
High Side PSI	345.0	
Low Side PSI	140.0	
Compressor Step Height	9.75" (25 cm)	
Compressor Step Width	7.88" (20 cm)	
Compressor Step Depth	21.0" (53 cm)	
Temperature Range	-13 to 23°F	

