accucold

ARG6PV



32.5" x 23.38" x 24.38" (H x W x D)

Performance series Pharma-Vac 6 cu.ft. freestanding ADA compliant glass door commercial all-refrigerator for the display and refrigeration of vaccines, with antimicrobial silver-ion handle and hospital grade cord with 'green dot' plug

Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

Product Features:

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs	
Commercial design	Meets UL-471 commercial standards	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup	
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment	

 \checkmark



accuceld

ARG6PV Specifications:

Nominal Height32.0" (81 cmHeight of Cabinet32.5" (83 cmNominal Width24.0" (61 cmWidth23.38" (59 cmWidth with Door Open23.88" (61 cmNominal Depth25.0" (64 cmDepth24.38" (62 cmDepth with Handle26.13" (66 cmDepth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomatinDoorGlassCabinetWhiteUS Electrical SafetyETL-CSafetyETL-C
Nominal Width24.0" (61 cmWidth23.38" (59 cmWidth with Door Open23.88" (61 cmNominal Depth25.0" (64 cmDepth24.38" (62 cmDepth with Handle26.13" (66 cmDepth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-C
Width23.38" (59 cmWidth with Door Open23.88" (61 cmNominal Depth25.0" (64 cmDepth24.38" (62 cmDepth with Handle26.13" (66 cmDepth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETL-C
Width with Door Open23.88" (61 cmNominal Depth25.0" (64 cmDepth24.38" (62 cmDepth with Handle26.13" (66 cmDepth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETL-CCanadian ElectricalETL-C
Nominal Depth25.0" (64 cmDepth24.38" (62 cmDepth with Handle26.13" (66 cmDepth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETL-CCanadian ElectricalETL-C
Depth24.38" (62 cmDepth with Handle26.13" (66 cmDepth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-C
Depth with Handle26.13" (66 cmDepth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-C
Depth with door at 90°46.5" (118 cmCapacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETICanadian ElectricalETL-C
Capacity6.0 cu.ft. (170 LDefrost TypeAutomaticDoorGlassCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-O
Defrost Type Automatic Door Glass Cabinet White US Electrical Safety ETI Canadian Electrical ETL-C
DoorGlassCabinetWhiteUS Electrical SafetyETICanadian ElectricalETL-C
Cabinet White US Electrical Safety ETI Canadian Electrical ETL-C
US Electrical Safety ETI Canadian Electrical ETL-C
Canadian Electrical ETL-C
Safety
Amps 0.75
Voltage/Frequency 115 V AC/60 Hz
Weight 119.0 lbs. (54 kg
Parts & Labor Warranty 2 Years
Compressor Warranty 5 Years
UPC 761101062563
Refrigerator Features
Door Swing RHE
Reversible Yes
Shelf Type Wire
Shelf Qty
Adjustable Shelves Yes
Thermostat Type Digita
Fan Type Interio
Refrigerant Type R600a
Refrigerant Amount 1.66oz
Interior Light Yes
Temperature Range 2 to 8°C
Sound Level 37.6 dE
Dimensions
Interior Height 24.5" (62 cm
Interior Width 20.0" (51 cm

Interior Depth	17.0" (43 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.0" (13 cm)





