# **ARG6PV-VT65MLSTACKMED2**



68" x 23.63" x 24.38" (H x W x D)

Stacked combination of ARG6PV all-refrigerator with antimicrobial silver ion handle and hospital grade 'green dot' cord and VT65MLBIMED2 manual defrost all-freezer for vaccine storage

### **Highlights:**

Independent refrigerator and freezer storage in one slimfitting footprint for space-challenged facilities

Intelligent microprocessor digital temperature controller for optimum temperature management

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

#### **Product Features:**

Space-saving design	Allows you to create a full refrigerator-freezer with independent controls in a slim-fitting footprint	
Easy assembly	Unit ships in three boxes for customer to install the StackRack on the bottom refrigerator/freezer and place and secure the other unit on top	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs	
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines	
+/-1°C Variation (refrigerator)	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C (refrigerator) and -20° to -15°C (freezer)	
Temperature alarms	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts (refrigerator)	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup  CH, INC.   ISO 9001:2015 Certified  CH, INC.   ISO 9001:2015 Certified  CH, INC.   ISO 9001:2015 Certified  CH, INC.   ISO 9001:2015 Certified	

# accuc@ld

## ARG6PV-VT65MLSTACKMED2 Specifications:

Overview			
Nominal Height	68.0" (173 cm)		
Height of Cabinet	68.0" (173 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.63" (60 cm)		
Nominal Depth	25.0" (64 cm)		
Depth	24.38" (62 cm)		
Depth with Handle	26.13" (66 cm)		
Capacity	9.2 cu.ft. (261 L)		
Door	Glass		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Voltage/Frequency	115 V AC/60 Hz		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101065854		
Refrigerator-Freezer			
Door Swing	RHD		
Reversible	Factory Reversible		
Adjustable Shelves	Yes		
Interior Light	Yes		
Refrigerator - Interior Height	24.5" (62 cm)		
Refrigerator - Interior Width	20.0" (51 cm)		
Refrigerator - Interior Depth	17.0" (43 cm)		
Refrigerator - Capacity	6.0 cu.ft		
Refrigerator - Shelf Type	Wire		
Refrigerator - Shelf Qty	4		
Refrigerator - Temperature Range	2 to 8°C		
Refrigerator - Refrigerant Type	R600a		
Refrigerator - Refrigerant Amount	1.66 oz.		
Freezer - Interior Height	24.25" (62 cm)		
Freezer - Interior Width	17.63" (45 cm)		
Freezer - Interior Depth	17.0" (43 cm)		
Freezer - Capacity	3.2 cu.ft		
Thermostat Type	Digital		

Fan Type	Interior
Freezer - Temperature Range	-12º to -25ºC
Freezer - Refrigerant Type	R134a
Freezer - Refrigerant Amount	2.76 oz.





