## SUMMIT

# SBC15NKCSS



34.25" x 15" x 22.5" (H x W x D)

15" wide, built-in, commercially listed kegerator, auto defrost with digital thermostat, front lock, sealed back, and complete stainless steel exterior

### **Highlights:**

Designed for built-in installation under the counter

Listed to NSF-7 standards and meets UL 471 for commercial use

15" wide design makes it ideal for smaller residential and commercial settings

#### **Product Features:**

15" wide design	Slim-fit design complements smaller commercial and residential spaces  ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings	
Commercially approved		
Built-in capability	Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require an extra ¼" of space due to the door design. For more information, see the user manual	
Versatile kegerator	2.9 cu.ft. interior can accept a 1/6 (sixtel) barrel keg or a corny keg; compatible with beer, wine, coffee, or kombucha tap systems	
Automatic defrost	Reduced user maintenance with auto defrost operation	
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit	
Tap cool system	Keeps cold air flowing to the tower for consistently cold beer	
Stainless steel floor cover	Interior includes steel cover to protect the floor when loading kegs	
Top guard rail (ships unassembled)	Attractive chrome guard rail helps to reduce spills and neaten service	





## SBC15NKCSS Specifications:

Overview		
Nominal Height	35.0" (89 cm)	
Height of Cabinet	34.25" (87 cm)	
Nominal Width	15.0" (38 cm)	
Width	15.0" (38 cm)	
Width with Door Open	15.25" (39 cm)	
Nominal Depth	23.0" (58 cm)	
Depth	22.5" (57 cm)	
Depth with Handle	24.5" (62 cm)	
Depth with door at 90°	36.5" (93 cm)	
Capacity	2.9 cu.ft. (82 L)	
Defrost Type	Automatic	
Door	Stainless Steel	
Cabinet	Stainless Steel	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Energy Usage/Year	280.0kWh/year	
Amps	1.25	
Voltage/Frequency	115 V AC/60 Hz	
Weight	80.0 lbs. (36 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101067865	
Kegerator		
Door Swing	RHD	
Reversible	Yes	
Adjustable Shelves	Yes	
Shelf Type	Chrome	
Shelf Qty	2	
Thermostat Type	Digital	
Fan Type	Exterior	
Refrigerant	R600a	
Refrigerant Amount	1.06 oz.	
High Side PSI	150.0	
Low Side PSI	50.0	
Inter Height	26.75" (68 cm)	
Interior Width	11.75" (30 cm)	
Interior Depth	17.5" (44 cm)	

Compressor Step Height	3.75" (10 cm)
Compressor Step Width	11.75" (30 cm)
Compressor Step Depth	5.0" (13 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	34° to 50° F





