## SUMMIT

# SBC15CF



34.25" x 15" x 22.5" (H x W x D)

15" wide, built-in, commercially listed coffee kegerator, auto defrost with digital thermostat, stainless steel door, front lock, black cabinet, sealed back, and includes all equipment necessary to dispense cold brew coffee

#### **Highlights:**

15" wide design makes it ideal for smaller residential and commercial settings

Listed to NSF-7 standards and meets UL 471 for commercial use

Designed for built-in installation under the counter

#### **Product Features:**

| 15" wide design  | Slim-fit design complements smaller commercial and residential spaces  |  |
|--|--|--|
| Commercially approved  | ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings   |  |
| Built-in capability  | Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require an extra ¼" of space due to the door design. For more information, see the user manual |  |
| Complete tap kit for serving cold brew coffee Commercially approved tap kit includes a stainless steel tower, Nitrogen tank, and regulator |  |  |
| Nitrogen tank included   | 5 lb. Nitrogen tank included (ships empty)   |  |
| Coffee dispenser   | 2.9 cu.ft. interior can accept a 1/6 (sixtel) coffee keg   |  |
| Automatic defrost  | Reduced user maintenance with auto defrost operation   |  |
| Digital thermostat   | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit  |  |
| Tap cool system  | Keeps cold air flowing to the tower for consistently cold coffee   |  |







### **SBC15CF Specifications:**

| Overview                      |                    |
|-------------------------------|--------------------|
| Height of Cabinet             | 34.25" (87 cm)     |
| Width                         | 15.0" (38 cm)      |
| Width with Door Open          | 15.25" (39 cm)     |
| Depth                         | 22.5" (57 cm)      |
| Depth with Handle             | 24.5" (62 cm)      |
| Depth with door at 90°        | 36.5" (93 cm)      |
| Capacity                      | 2.9 cu.ft. (82 L)  |
| Defrost Type                  | Automatic          |
| Door                          | Stainless Steel    |
| Cabinet                       | Black              |
| US Electrical Safety          | ETL                |
| Canadian Electrical<br>Safety | ETL-C              |
| Sanitation                    | ETL-S              |
| Energy Usage/Year             | 280.0kWh/year      |
| Amps                          | 1.25               |
| Voltage/Frequency             | 115 V AC/60 Hz     |
| Weight                        | 78.0 lbs. (35 kg)  |
| Shipping Weight               | 120.0 lbs. (54 kg) |
| Parts & Labor Warranty        | 1 Year             |
| Compressor Warranty           | 5 Years            |
| UPC                           | 761101067902       |
| Kegerator                     |                    |
| Door Swing                    | RHD                |
| Reversible                    | Yes                |
| Tap Kit                       | Yes                |
| Height with Tap               | 49.75" (126 cm)    |
| Number of Taps                | 1                  |
| Adjustable Shelves            | Yes                |
| Shelf Type                    | Chrome             |
| Shelf Qty                     | 2                  |
| Thermostat Type               | Digital            |
| Fan Type                      | Exterior           |
| Refrigerant                   | R600a              |
| Refrigerant Amount            | 1.06 oz.           |
| High Side PSI                 | 150.0              |
| Low Side PSI                  | 50.0               |
| Inter Height                  | 26.75" (68 cm)     |

| Interior Width         | 11.75" (30 cm) |
|------------------------|----------------|
| Interior Depth         | 17.5" (44 cm)  |
| Compressor Step Height | 3.75" (10 cm)  |
| Compressor Step Width  | 11.75" (30 cm) |
| Compressor Step Depth  | 5.0" (13 cm)   |
| Level Legs Qty         | 4              |
| Wheel Qty              | 4              |
| Temperature Range      | 34° to 50° F   |





