# accucold

# AL751WLBI



## 32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in undercounter all-refrigerator for general purpose use, with lock, auto defrost operation and white exterior

#### **Highlights:**

32" height for use under lower ADA compliant counters

Flexible design allows built-in or freestanding use in 24" spaces

Factory-installed lock provides security you can count on

### **Product Features:**

| ADA compliant                | 32 inch height fits under standard ADA counters   |  |
|------------------------------|---|--|
| Slim undercounter dimensions | Less than 24 inches wide with a full 5.5 c.f. capacity  |  |
| Built-in capable             | Make the best use of space by installing your appliance under the counter and flush with other cabinets |  |
| Fully finished white cabinet | Allows the unit to be used freestanding   |  |
| Factory installed lock       | Keyed lock offers added security  |  |
| Reversible door              | User-reversible door swing for added flexibility  |  |
| Automatic defrost            | Reduced user maintenance with automatic defrost operation   |  |
| Hidden evaporator            | Cold wall design with hidden evaporator and seamless interior   |  |
| One piece interior liner     | Easy clean-up with a seamless liner that won't hold a mess in hidden crevices                           |  |





# accuceld

## AL751WLBI Specifications:

| Nominal Height   | 32.0" (81 cm)   |  |  |
|--|---|--|--|
| Height of Cabinet  | 32.0" (81 cm)   |  |  |
| Height to Hinge Cap  | 32.25" (82 cm)  |  |  |
| Nominal Width  | 24.0" (61 cm)   |  |  |
| Width  | 23.63" (60 cm)  |  |  |
| Nominal Depth  | 24.0" (61 cm)   |  |  |
| Depth  | 23.5" (60 cm)   |  |  |
| Depth with Handle  | 24.0" (61 cm)   |  |  |
| Depth with door at 90°   | 45.13" (115 cm)   |  |  |
| Capacity   | 5.5 cu.ft. (156 L)  |  |  |
| Defrost Type   | Automatic   |  |  |
| Door   | White   |  |  |
| Cabinet  | White   |  |  |
| US Electrical Safety   | ETL   |  |  |
| Canadian Electrical<br>Safety  | ETL-C   |  |  |
| Amps   | 1.4   |  |  |
| Voltage/Frequency  | 115 V AC/60 Hz  |  |  |
| Weight   | 100.0 lbs. (45 kg)  |  |  |
| Parts & Labor Warranty   | 1 Year  |  |  |
| Compressor Warranty  | 5 Years   |  |  |
| UPC  | 761101071831  |  |  |
| Refrigerator Features  |   |  |  |
| Door Swing   | RHD   |  |  |
| Reversible   | Yes   |  |  |
| Shelf Type   | Wire  |  |  |
|  | 3   |  |  |
| Shelf Qty  | 0   |  |  |
| Shelf Qty<br>Adjustable Shelves  | Yes   |  |  |
|  |   |  |  |
| Adjustable Shelves   | Yes   |  |  |
| Adjustable Shelves<br>Thermostat Type  | Yes<br>Dial   |  |  |
| Adjustable Shelves<br>Thermostat Type<br>Fan Type  | Yes<br>Dial<br>Exterior   |  |  |
| Adjustable Shelves<br>Thermostat Type<br>Fan Type<br>Refrigerant Type  | Yes<br>Dial<br>Exterior<br>R600a                                  |  |  |
| Adjustable Shelves<br>Thermostat Type<br>Fan Type<br>Refrigerant Type<br>Refrigerant Amount  | Yes<br>Dial<br>Exterior<br>R600a<br>0.64oz.                       |  |  |
| Adjustable Shelves<br>Thermostat Type<br>Fan Type<br>Refrigerant Type<br>Refrigerant Amount<br>High Side PSI                                   | Yes<br>Dial<br>Exterior<br>R600a<br>0.64oz.<br>180.0              |  |  |
| Adjustable Shelves<br>Thermostat Type<br>Fan Type<br>Refrigerant Type<br>Refrigerant Amount<br>High Side PSI<br>Low Side PSI                   | Yes<br>Dial<br>Exterior<br>R600a<br>0.64oz.<br>180.0<br>80.0      |  |  |
| Adjustable Shelves<br>Thermostat Type<br>Fan Type<br>Refrigerant Type<br>Refrigerant Amount<br>High Side PSI<br>Low Side PSI<br>Level Legs Qty | Yes<br>Dial<br>Exterior<br>R600a<br>0.64oz.<br>180.0<br>80.0<br>4 |  |  |

| Interior Width         | 21.0" (53 cm)  |
|------------------------|----------------|
| Interior Depth         | 17.75" (45 cm) |
| Compressor Step Height | 5.5" (14 cm)   |
| Compressor Step Width  | 21.0" (53 cm)  |
| Compressor Step Depth  | 5.5" (14 cm)   |
|                        |                |





SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

