accucold

FF7LWBIMED2



33.75" x 23.63" x 23" (H x W x D)

Built-in undercounter auto defrost medical/scientific allrefrigerator with front control panel equipped with a digital thermostat and NIST calibrated thermometer/alarm; includes front lock, hospital grade cord, and internal fan

Highlights:

Specially designed and featured to meet the CDC, VFC and VFA's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Flexible design allows built-in or freestanding use in 24" wide spaces

Product Features:

Reliable temperature stability	Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions	
Built-in capable	Front-breathing system allows the unit to be used built-in	
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines	
Factory installed lock	Keyed lock conveniently located towards the top of the door for added security (2 keys included)	
Automatic defrost	Reduced maintenance with auto defrost system	
Internal fan	Fan-forced cooling ensures the unit is evenly cooled from top to bottom	
SUMMIT APPLIANCE DIVISION, FELIX STO 770 Garrison Avenue Bronx, NY 10474 USA TEL 7		

accuceld

FF7LWBIMED2 Specifications:

Overview			
Nominal Height	34.0" (86 cm)		
Height of Cabinet	33.75" (86 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.63" (60 cm)		
Nominal Depth	23.0" (58 cm)		
Depth	23.0" (58 cm)		
Depth with Handle	25.0" (64 cm)		
Depth with door at 90°	45.75" (116 cm)		
Capacity	5.5 cu.ft. (156 L)		
Defrost Type	Automatic		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	1.3		
Voltage/Frequency	115 V AC/60 Hz		
Weight	100.0 lbs. (45 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101072456		
Refrigerator Features			
Door Swing	RHD		
Reversible	Factory Reversible		
Shelf Type	Wire		
Shelf Qty	3		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior and Exterior		
Refrigerant Type	R600a		
Refrigerant Amount	0.64oz.		
High Side PSI	180.0		
Low Side PSI	80.0		
Level Legs Qty	4		
Interior Light	Yes		
Temperature Range	2º to 8ºC		
Dimensions			
Interior Height	26.25" (67 cm)		

Interior Width	21.0" (53 cm)
Interior Depth	18.0" (46 cm)
Compressor Step Height	5.5" (14 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)



