

SBC58BLBIADACFTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap cold brew coffee dispenser with stainless steel wrapped door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Dual tap commercial grade tap kit includes everything you need to serve flat cold brew coffee on draft

Commercially listed to NSF-7 standards

Product Features:

| | |
|------------------------------|--|
| ADA compliant height | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters |
| Commercially approved | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings |
| Built-in capable | Front-breathing design allows fully recessed installation under counters |
| Complete dual tap kit | Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs |
| Stainless steel wrapped door | 304 grade stainless steel for a professional look with lasting durability |
| Professional handle | Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally |
| Adjustable thermostat | Interior dial thermostat ensures easy temperature management |
| Automatic defrost | No-frost operation for minimum user maintenance |
| Reversible door | User-reversible door swing allows you to easily adjust to better accommodate your setting |



SBC58BLBIADACFTWIN Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.25" (82 cm) |
| Width | 23.63" (60 cm) |
| Depth | 22.75" (58 cm) |
| Depth with Handle | 24.25" (62 cm) |
| Depth with door at 90° | 45.0" (114 cm) |
| Capacity | 5.5 cu.ft. (156 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.2 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 110.0 lbs. (50 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101069623 |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Tap Kit | Yes |
| Height with Tap | 47.5" (121 cm) |
| Number of Taps | 2 |
| Thermostat Type | Dial |
| Interior Light | Yes |
| Fan Type | Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 0.64 oz. |
| High Side PSI | 180.0 |
| Low Side PSI | 80.0 |
| Inter Height | 25.75" (65 cm) |
| Interior Width | 21.0" (53 cm) |
| Interior Depth | 17.75" (45 cm) |
| Compressor Step Height | 6.5" (17 cm) |
| Compressor Step Width | 21.0" (53 cm) |

| | |
|-----------------------|--------------|
| Compressor Step Depth | 5.5" (14 cm) |
| Temperature Range | 34° to 43°F |

