

SBC58BLBIADACMTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap combo nitro/cold brew coffee dispenser with stainless steel door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro cold brew drafts

Commercially listed to NSF-7 standards

Product Features:

| | |
|--------------------------------------|---|
| Dispenses both flat and nitro coffee | Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts |
| ADA compliant height | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters |
| Built-in capable | Front-breathing design allows fully recessed installation under counters |
| Commercially approved | Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs |
| Complete tap kit | Commercial grade tap kit includes a stainless steel stout tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs |
| Dual tap system | Twin style draft tower allows you to serve from two cornelius style kegs |
| Stainless steel wrapped door | 304 grade stainless steel for a professional look with lasting durability |
| Professional handle | Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally |
| Adjustable thermostat | Interior dial thermostat ensures easy temperature management |



SBC58BLBIADACMTWIN Specifications:

| Overview | |
|----------------------------|--------------------|
| Nominal Height | 32.0" (81 cm) |
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.25" (82 cm) |
| Nominal Width | 24.0" (61 cm) |
| Width | 23.63" (60 cm) |
| Nominal Depth | 23.0" (58 cm) |
| Depth | 22.75" (58 cm) |
| Depth with Handle | 24.25" (62 cm) |
| Depth with door at 90° | 45.0" (114 cm) |
| Capacity | 5.5 cu.ft. (156 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.2 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 110.0 lbs. (50 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101069630 |
| Kegerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Tap Kit | Yes |
| Number of Taps | 2 |
| Thermostat Type | Dial |
| Interior Light | Yes |
| Fan Type | Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 0.64 oz. |
| High Side PSI | 180.0 |
| Low Side PSI | 80.0 |
| Inter Height | 25.75" (65 cm) |
| Interior Width | 21.0" (53 cm) |
| Interior Depth | 17.75" (45 cm) |

| | |
|------------------------|---------------|
| Compressor Step Height | 6.5" (17 cm) |
| Compressor Step Width | 21.0" (53 cm) |
| Compressor Step Depth | 5.5" (14 cm) |
| Temperature Range | 34° to 43°F |

